



INDUSTRIAL BATTERIES

MITSUBISHI

WALKIE, RIDER/WALKIE, TOW TRACTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
NTT90T, PLDM20, PLDM20A	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	12	SB6325
PLDM20B, PLDM30, PLDM30A	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	12	SB6325
PLDM30B	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	12	SB6325
32 x 8.0625 x 23.5	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	12	SB6325
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	12	SB6325
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	12	SB6325
NTT90TA, PLDM20AA	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	12	SB6325
PLDM20BA, PLDM300BA	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	12	SB6325
PLDM30AA	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	12	SB6325
32 x 13.25 x 23.5	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	12	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	12	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	12	SB6325
NTT90T	12	6-D85-25		11.87	1020	85	1215	31	12.875	23.25	1027	X		B	12	SB6325
32 x 13.25 x 23.375	12	6-D85-25		11.87	1020	85	1040	28.9375	12.875	23.25	999	X		B	12	SB6325
	12	6-H80-25		11.17	960	80	1215	31	12.875	23.25	986	X		B	12	SB6325
	12	6-H80-25		11.17	960	80	1040	28.9375	12.875	23.25	959	X		B	12	SB6325
	12	6-P95-25		13.27	1140	95	1215	31	12.875	23.25	1037	X		B	12	SB6325
	12	6-P95-25		13.27	1140	95	1040	28.9375	12.875	23.25	1009	X		B	12	SB6325
	NTT100	48	24-D35-11		8.15	175	35	7092	34.5625	19	13	851	X		B	15
35.1875 x 19.0625 x 14.75																
NTF200PN**													X	A	12	SB6325
35.5625 x 26.5625 x 17.875																

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate KWH	A.H.	AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length Pos. (in.)		Standard Conn.	
							Length X	Width Y	Height Z		Yes	No				
PMW20 29.375 x 8.875 x 26.5	24	12-D100-5	cm	4.66	200	100	3526	24.25	8.3125	26.1875	514	X		B	12	SB6325
	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	12	SB6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	12	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	12	SB6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	12	SB6325
PMW30 32 x 9.1875 x 24	24	12-D85-7		5.94	255	85	3447	30.5	8.5625	23.25	595	X		B	18	SB6325
	24	12-D85-7	cm	5.94	255	85	3415	30.5	8.5625	23.1875	606	X		B	18	SB6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	18	SB6325
	24	12-H80-7		5.59	240	80	3447	30.5	8.5625	23.25	571	X		B	18	SB6325
	24	12-H80-7	cm	5.59	240	80	3415	30.5	8.5625	23.1875	582	X		B	18	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	18	SB6325
	24	12-P95-7		6.63	285	95	3447	30.5	8.5625	23.25	601	X		B	18	SB6325
	24	12-P95-7	cm	6.63	285	95	3415	30.5	8.5625	23.1875	612	X		B	18	SB6325
PMWR30, PMWR40 31.9375 x 13.5 x 30.9375	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
PMCR30, PMW30 (Optional Compartment) 32 x 13.4375 x 24	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	18	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	18	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)		
PMCR40 31.5 x 13.4375 x 31.5	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	18	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	18	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	18	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	18	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	18	SB6325
24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325	
PMWS15 31.875 x 13.375 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	18	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	18	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	18	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	18	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	18	SB6325
24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325	
PMT90, PMT, PMWS15 PMWT15, PMWT20 31.5 x 13.4375 x 24 Min. Battery Wt. - 975 lbs.	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	18	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	18	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325	
PMWT15N, PMWT18N 25.25 x 11.25 x 25.5	24	12-D85-9		7.92	340	85	3150	25.1875	10.8125	22.5625	696		X	A	12	SB6325
	24	12-H80-9		7.45	320	80	3150	25.1875	10.8125	22.5625	668		X	A	12	SB6325
	24	12-P95-9		8.85	380	95	3150	25.1875	10.8125	22.5625	703		X	A	12	SB6325
PMW23N 26.25 x 8.75 x 25	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		A	18	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		A	18	SB6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		A	18	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
PMW23NL 31.25 x 8.75 x 31.25	24	12-D100-7	6.98	300	100	3456	30.5	8.5625	26.1875	672	X		A	18	SB6325
	24	12-D100-7	6.98	300	100	3346	30.5	8.5625	26.1875	686	X		A	24	SB6325
	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		A	18	SB6325
	24	12-D125-7	8.73	375	125	3824	29.1875	8.6875	31.125	851	X		A	18	SB6325
	24	12-D125-7	8.73	375	125	3329	25.3125	8.5625	31.0625	792	X		A	18	SB6325
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		A	18	SB6325
	24	12-H120-7	8.38	360	120	3824	29.1875	8.6875	31.125	842	X		A	18	SB6325
	24	12-H120-7	8.38	360	120	3329	25.3125	8.5625	31.0625	784	X		A	18	SB6325
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		A	18	SB6325
	24	12-P140-7	9.78	420	140	3824	29.1875	8.6875	31.125	860	X		A	18	SB6325
	24	12-P140-7	9.78	420	140	3329	25.3125	8.5625	31.0625	800	X		A	18	SB6325
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		A	18	SB6325
	PMW30N 25.25 x 8.875 x 25 Min. Battery Wt. - 485 lbs.	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	18
24		12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	18	SB6325
24		12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	18	SB6325
PMW30NL 31.5 x 13.5 x 31.1875	24	12-D100-11	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
	24	12-H80-11	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
	24	12-P95-11	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	18	SB6325
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	18	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	18	SB6325
24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325	
PW23, PW30 26.8125 x 9.375 x 26.625	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		A	18	SB6325
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		A	18	SB6325
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		A	18	SB6325
PMWT15N, PMWT18N 28.25 x 11 x 23.625 See Note A	24	12-D85-9	7.92	340	85	3150	25.1875	10.8125	22.5625	696		X	A	12	SB6325
	24	12-H80-9	7.45	320	80	3150	25.1875	10.8125	22.5625	668		X	A	12	SB6325
	24	12-P95-9	8.85	380	95	3150	25.1875	10.8125	22.5625	703		X	A	12	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

cm - Charge-Mate includes on board charger.

** Contact EPM factory for new battery tray design required for 24-D45-15 (35.19 x 25.56 x 23.25).

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Note A - Battery compartment includes spacer to accommodate smaller battery.

STRADDLE, STRADDLE REACH TRUCKS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FBR12, FBRW12 38.5 x 13.1875 x 22.5625	24	12-D65-15	10.59	455	65	3449	35.0625	12.875	20	1017		X	D	18	SB6325
	24	12-D85-15 dh	13.85	595	85	3204	35.0625	12.875	21.625			X	D	18	SB6325
	24	12-H80-15 dh	13.04	560	80	3204	35.0625	12.875	21.625			X	D	18	SB6325
	24	12-P95-15 dh	15.48	665	95	3204	35.0625	12.875	21.625			X	D	18	SB6325
FBR13, FBRW13 38 x 13.1875 x 23.5	24	12-D85-15	13.85	595	85	3056	35.0625	12.875	22.625	1178		X	D	18	SB6325
	24	12-H80-15	13.04	560	80	3056	35.0625	12.875	22.625	1131		X	D	18	SB6325
	24	12-P95-15	15.48	665	95	3056	35.0625	12.875	22.625	1190		X	D	18	SB6325
FBR15, FBR18, FBRW15 FBRW18 37.875 x 18.5 x 23.5	48	24-D85-11	19.79	425	85	7158	37.8125	17.5625	22.6875	1730		X	D	18	SB6325
	48	24-H80-11	18.62	400	80	7158	37.8125	17.5625	22.6875	1661		X	D	18	SB6325
	48	24-P95-11	22.12	475	95	7158	37.8125	17.5625	22.6875	1747		X	D	18	SB6325
FER3000LD, FER3000LD-15D FER4000LD, FER4000LD-20D 38.5 x 16.625 x 32.5625	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	C	18	SB6320
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	C	18	SB6320
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	C	18	SB6320
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	C	18	SB6320
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	C	18	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	C	18	SB6320
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	C	18	SB6320
FER3000LC, FER3000LC-15C FER4000LC, FER4000LC-20C 38.5 x 16.625 x 32.25	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	C	18	SB6322
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	C	18	SB6322
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	C	18	SB6322
EDR13N, EDR24, ESR15N ESR18N, ESR20N, ESR24 ESS15N, ESS20N, ESS24 38.625 x 14.25 x 31.625	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	12	SB6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	12	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	12	SB6322
EDR24, ESR24, ESS24 ESS24-15, ESS24-20 38.625 x 16.25 x 31.625	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	12	SB6322
	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	12	SB6322
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	12	SB6322

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
EDR15HN, EDR15N, EDR36	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	12	SB6320
ESR18N, ESR20HN, ESR20N	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	12	SB6320
ESR23HN, ESR23N, ESR36	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	12	SB6320
ESS20N, ESS36 38.625 x 16.25 x 31.625															
ESR36, EDR36, ESS36	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	12	SB6320
ESS36-15, ESS36-20	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	12	SB6320
38.625 x 21.5 x 31.625 Optional Compartment	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	12	SB6320
EDR13N, ESR15N, ESS15N	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	12	SB6320
38.625 x 14.25 x 31.6875	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	12	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	12	SB6320

dh - Special tray design IST3204 includes drop handles. Overall height to top of terminal is 22.06".
H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

ORDER PICKERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
EOP15-24	24	12-D125-13	17.46	750	125	3093	30.5625	12.75	30.5	1444		X	C	12	SB6322
31.5 x 13.25 x 32.25	24	12-H120-13	16.76	720	120	3093	30.5625	12.75	30.5	1430		X	C	12	SB6322
	24	12-P140-13	19.56	840	140	3093	30.5625	12.75	30.5	1458		X	C	12	SB6322
EOP15-24P	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	C	12	SB6322
36.75 x 14.5 x 32.25	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	C	12	SB6322
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	C	12	SB6322

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)		
FBC15KS, FBC18KS 38.5 x 18.5 x 32.25	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	15	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	15	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	15	SB6320
FBC15KS, FBC18KS 38.5 x 16.25 x 32.25	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	15	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	15	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	15	SB6320
FBC15KS, FBC18KS 38.5 x 13.5625 x 32.25	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	15	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	15	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	15	SB6320
FBC20KS 38.5 x 21.25 x 32.25	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	15	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	15	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	15	SB6320
FBC20KS 38.5 x 18.5 x 32.25	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	15	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	15	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	15	SB6320
FBC25KS 38.5 x 23.75 x 32.25	36	18-D125-19	39.29	1125	125	6089	38.1875	22.3125	30.5625	3106		X	B	15	SB6320
	36	18-H120-19	37.71	1080	120	6089	38.1875	22.3125	30.5625	3075		X	B	15	SB6320
	36	18-P140-19	44.00	1260	140	6089	38.1875	22.3125	30.5625	3137		X	B	15	SB6320
FBC15NS, FBC18NS 38.625 x 16.25 x 31.75	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	A	20	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	A	20	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	A	20	SB6320
FBC20NS 38.625 x 21.25 x 31.75	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	A	20	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	A	20	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	A	20	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FEF2000, FEF2500	24	12-D85-19	17.81	765	85	3096	38.0625	14.875	22.625	1494		X	B	18	SB6322
FET2000-10C, FET2000-13C	24	12-H80-19	16.76	720	80	3096	38.0625	14.875	22.625	1434		X	B	18	SB6322
FET2500-10C, FET2500-13C 39.25 x 15.5 x 25.5	24	12-P95-19	19.90	855	95	3096	38.0625	14.875	22.625	1509		X	B	18	SB6322
FEF3000, FEF3500	24	12-D85-25	23.75	1020	85	3076	38.1875	19.5	22.6875	1970		X	B	18	SB6322
FET3000-15C, FET3000-18C	24	12-H80-25	22.35	960	80	3076	38.1875	19.5	22.6875	1891		X	B	18	SB6322
FET3500-15C, FET3500-18C 39.25 x 21.375 x 25.5	24	12-P95-25	26.54	1140	95	3076	38.1875	19.5	22.6875	1990		X	B	18	SB6322
FB15P 38.375 x 26.375 x 18.6875	48	24-D55-15	17.93	385	55	7033	38.1875	23.5625	18.1875	1761		X	B	18	SB6325
FB20P, FB25P 38.375 x 29 x 23.0625	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	18	SB6321
	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	18	SB6321
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	18	SB6321
FE3000LB, FE4000LB	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	18	SB6320
FE5000LB	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	18	SB6320
39.25 x 28 x 23.125	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	18	SB6320
FE3000LB, FE4000LB	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	18	SB6321
FE5000LB	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	18	SB6321
39.25 x 28 x 23.125	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	18	SB6321
FE15C, FE20C, FE25C	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	18	SB6320
39.1875 x 28 x 23.25	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	18	SB6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FE15C, FE20C, FE25C 39.1875 x 28 x 23.25	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	18	SB6320
	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	18	SB6320
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	18	SB6320
FE6000LB 39.25 x 33.25 x 23.125	72	36-D85-13	35.62	510	85	8002	37.8125	30.6875	22.6875	3059		X	B	30	SB6320
	72	36-H80-13	33.52	480	80	8002	37.8125	30.6875	22.6875	2937		X	B	30	SB6320
	72	36-P95-13	39.81	570	95	8002	37.8125	30.6875	22.6875	3090		X	B	30	SB6320
FE30C 39.1875 x 33.6875 x 23.25	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	18	SB6320
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	18	SB6320
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	18	SB6320
FE30C 39.1875 x 33.6875 x 23.25	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	18	SB6320
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	18	SB6320
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	18	SB6320
FBC15 36.375 x 26.6875 x 22.6875	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	18	SB6320
	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	18	SB6320
	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	18	SB6320
FBC15 36.375 x 26.6875 x 22.6875	48	24-D85-15	27.70	595	85	7049	35.1875	25.5625	22.6875	2332		X	B	18	SB6320
	48	24-H80-15	26.07	560	80	7049	35.1875	25.5625	22.6875	2239		X	B	18	SB6320
	48	24-P95-15	30.96	665	95	7049	35.1875	25.5625	22.6875	2355		X	B	18	SB6320
FBC20, FBC20K, FBC25 FBC25K 39.9375 x 30.5625 x 22.6875	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	18	SB6320
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	18	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	18	SB6320
FBC20, FBC20K, FBC25 FBC25K 39.9375 x 30.5625 x 22.6875	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	18	SB6320
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	18	SB6320
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	18	SB6320
FBC25, FBC30 40.6875 x 36.6875 x 22.6875	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3619		X	B	18	SB6320
	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3474		X	B	18	SB6320
	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3655		X	B	18	SB6320
FBC25, FBC30 40.6875 x 36.6875 x 22.6875	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573		X	B	18	SB6320
	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430		X	B	18	SB6320
	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609		X	B	18	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
2FBC15, 2FBC18, FBC15K	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	24	SB6320
FBC15N, FBC18, FBC18K	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	24	SB6320
FBC18KL, FBC18LN, FBC18N	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	24	SB6320
35.6875 x 27.6875 x 23.25															
2FBC15, 2FBC18, FBC15K	48	24-D85-15	27.70	595	85	7049	35.1875	25.5625	22.6875	2332		X	B	24	SB6321
FBC15N, FBC18, FBC18K	48	24-H80-15	26.07	560	80	7049	35.1875	25.5625	22.6875	2239		X	B	24	SB6321
FBC18KL, FBC18LN, FBC18N	48	24-P95-15	30.96	665	95	7049	35.1875	25.5625	22.6875	2355		X	B	24	SB6321
35.6875 x 27.6875 x 23.25															
2FBC20, FBC20N, FBC25N	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	24	SB6320
38.875 x 30.5 x 23.25	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	24	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	24	SB6320
2FBC20, FBC20N, FBC25N	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	24	SB6321
38.875 x 30.5 x 23.25	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	24	SB6321
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	24	SB6321
2FBC25	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	24	SB6320
38.875 x 30.5 x 23.25	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	24	SB6320
Min. Battery Wt. - 2900 lbs.	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	24	SB6320
2FBC25	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	24	SB6321
38.875 x 30.5 x 23.25	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	24	SB6321
Min. Battery Wt. - 2900 lbs.	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	24	SB6321
2FBC25E, 2FBC30, FBC25E	36	18-D85-29	41.55	1190	85	6021	38.1875	33.6875	22.6875	3394		X	B	24	SB6320
FBC25EN, FBC25KE	36	18-H80-29	39.11	1120	80	6021	38.1875	33.6875	22.6875	3258		X	B	24	SB6320
FBC25KL, FBC25LN, FBC30	36	18-P95-29	46.44	1330	95	6021	38.1875	33.6875	22.6875	3428		X	B	24	SB6320
FBC30K, FBC30KL, FBC30LN															
FBC30N															
38.875 x 34.375 x 23.25															
Min. Battery Wt. - 3100 lbs.															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
2FBC25E, 2FBC30, FBC25E	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	24	SB6321
FBC25EN, FBC25KE	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	24	SB6321
FBC25KL, FBC25LN, FBC30	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	24	SB6321
FBC30K, FBC30KL, FBC30LN FBC30N 38.875 x 34.375 x 23.25 Min. Battery Wt. - 3100 lbs.															
FBC35N, FBC40N, FBC45N	36	18-D85-33	47.49	1360	85	6818	40	40	22.6875	3766		X	B	30	SB6320
FBC55N	36	18-D85-33	47.49	1360	85	6065	38.1875	38.1875	22.6875	3887		X	B	30	SB6320
46.125 x 40.625 x 24.3125	36	18-H80-33	44.70	1280	80	6818	40	40	22.6875	3615		X	B	30	SB6320
Min. Battery Wt. - 3600 lbs.	36	18-H80-33	44.70	1280	80	6065	38.1875	38.1875	22.6875	3732		X	B	30	SB6320
	36	18-P95-33	53.08	1520	95	6818	40	40	22.6875	3804		X	B	30	SB6320
	36	18-P95-33	53.08	1520	95	6065	38.1875	38.1875	22.6875	3926		X	B	30	SB6320
FBC35N, FBC40N, FBC45N	48	24-D85-29	55.41	1190	85	7067	44.6875	38.1875	22.6875	4497		X	B	30	SB6321
FBC55N	48	24-H80-29	52.15	1120	80	7067	44.6875	38.1875	22.6875	4317		X	B	30	SB6321
46.125 x 40.625 x 24.3125	48	24-P95-29	61.92	1330	95	7067	44.6875	38.1875	22.6875	4542		X	B	30	SB6321
Min. Battery Wt. - 3600 lbs.															
FBP20K	80	40-D125-9	38.80	500	125	9185	39.75	26.75	30.5625	3447		X	B	16	SB6320
40.75 x 28.3125 x 30.9375	80	40-H120-9	37.25	480	120	9185	39.75	26.75	30.5625	3413		X	B	16	SB6320
Min. Battery Wt. - 3050 lbs.	80	40-P140-9	43.46	560	140	9185	39.75	26.75	30.5625	3481		X	B	16	SB6320
FBP30K, FBP35K	80	40-D125-13	58.20	750	125	9115	40.6875	31.625	30.5625	4664		X	B	16	SB6320
40.75 x 33.9375 x 30.9375	80	40-H120-13	55.87	720	120	9115	40.6875	31.625	30.5625	4617		X	B	16	SB6320
Min. Battery Wt. - 4123 lbs.	80	40-P140-13	65.18	840	140	9115	40.6875	31.625	30.5625	4711		X	B	16	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS - 3 WHEEL

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
FET10, FET13 39.3125 x 16.125 x 25.5	36	18-D85-13	17.81	510	85	6062	37.6875	15.4375	22.625	1507		X	B	18	SB6320
	36	18-H80-13	16.76	480	80	6062	37.6875	15.4375	22.625	1447		X	B	18	SB6320
	36	18-P95-13	19.90	570	95	6062	37.6875	15.4375	22.625	1522		X	B	18	SB6320
FET15, FET18 39.3125 x 22.8125 x 25.5	36	18-D85-19	26.71	765	85	6041	38.1875	22.3125	22.6875	2242		X	B	18	SB6320
	36	18-H80-19	25.14	720	80	6041	38.1875	22.3125	22.6875	2152		X	B	18	SB6320
	36	18-P95-19	29.86	855	95	6041	38.1875	22.3125	22.6875	2264		X	B	18	SB6320
FBS15 39.5625 x 20.75 x 24.5625	36	18-D85-17	23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	D	30	SB6320
	36	18-H80-17	22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	D	30	SB6320
	36	18-P95-17	26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	D	30	SB6320
FBS15 39.5625 x 20.75 x 24.5625	48	24-D85-13	23.75	510	85	7017	37.8125	20.5625	22.6875	2030		X	D	30	SB6321
	48	24-H80-13	22.35	480	80	7017	37.8125	20.5625	22.6875	1949		X	D	30	SB6321
	48	24-P95-13	26.54	570	95	7017	37.8125	20.5625	22.6875	2050		X	D	30	SB6321
FBS18, FBS20 39.5625 x 25 x 24.5625	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	D	30	SB6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	D	30	SB6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	D	30	SB6320
FBS18, FBS20 39.5625 x 25 x 24.5625	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	D	30	SB6321
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	D	30	SB6321
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	D	30	SB6321
FB16KT, FB16NT 40 x 20.875 x 24.75	36	18-D85-17	23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	B	20	SB6320
	36	18-H80-17	22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	B	20	SB6320
	36	18-P95-17	26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	B	20	SB6320
FB16KT, FB16NT 40 x 20.875 x 24.75	48	24-D85-13	23.75	510	85	7017	37.8125	20.5625	22.6875	2030		X	B	20	SB6320
	48	24-H80-13	22.35	480	80	7017	37.8125	20.5625	22.6875	1949		X	B	20	SB6320
	48	24-P95-13	26.54	570	95	7017	37.8125	20.5625	22.6875	2050		X	B	20	SB6320
FB18KT, FB18NT, FB20KT 40 x 25 x 24.75	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	20	SB6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	20	SB6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	20	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS - 3 WHEEL (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
FB18KT, FB20KT, FB20NT 40 x 25 x 24.75	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	B	20	SB6320
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	B	20	SB6320
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	B	20	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.