



INDUSTRIAL BATTERIES

YALE

WALKIE, RIDER/WALKIE, TOW TRACTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
MP30, MP30A, MP40A	24	12-D85-5	3.96	170	85	3068	24.75	6.4375	22.5625	412		X	B	18	SB6325
MPB30, MPB30A, MPB40A	24	12-H80-5	3.72	160	80	3068	24.75	6.4375	22.5625	396		X	B	18	SB6325
MPB40AC 29.5 x 7.5625 x 25.375	24	12-P95-5	4.42	190	95	3068	24.75	6.4375	22.5625	416		X	B	18	SB6325
ML40, ML60, MP100, MP40	12	6-D85-13	5.94	510	85	1069	30.5625	7.75	22.5625	578		X	B	21	SB6325
MP40HP, MP60, MP60HP	12	6-H80-13	5.59	480	80	1069	30.5625	7.75	22.5625	555		X	B	21	SB6325
MP80 32 x 8.0625 x 24	12	6-P95-13	6.63	570	95	1069	30.5625	7.75	22.5625	584		X	B	21	SB6325
MLE40, MLE60, MLW40	12	6-D85-11	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6325
MLW45D, MLW60, MPE40	12	6-H80-11	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6325
MPE60, MPW40, MPW60	12	6-P95-11	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6325
32 x 8.25 x Open	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	21	SB6325
	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	21	SB6325
	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	21	SB6325
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	21	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	21	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	21	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	21	SB6325
ML100, ML40, ML60, ML80	12	6-D85-25	11.87	1020	85	1031	28.9375	12.875	22.625	983		X	B	24	SB6325
MO40HP, MO60HP, MP100	12	6-H80-25	11.17	960	80	1031	28.9375	12.875	22.625	944		X	B	24	SB6325
MP40, MP60, MP80 32 x 13.375 x 24	12	6-P95-25	13.27	1140	95	1031	28.9375	12.875	22.625	993		X	B	24	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
ML100, ML40, ML60, ML80	24	12-D85-11	cm	9.89	425	85	3322	31.375	12.875	22.75	939		X	B	30	SB6325
MO40HP, MO60HP, MP100	24	12-H80-11	cm	9.31	400	80	3322	31.375	12.875	22.75	901		X	B	30	SB6325
MP40, MP60, MP80	24	12-P95-11	cm	11.06	475	95	3322	31.375	12.875	22.75	948		X	B	30	SB6325
32 x 13.375 x 24	24	12-D85-13		11.87	510	85	3082	30.5625	12.75	22.625	1025		X	B	24	SB6325
	24	12-H80-13		11.17	480	80	3082	30.5625	12.75	22.625	984		X	B	24	SB6325
	24	12-P95-13		13.27	570	95	3082	30.5625	12.75	22.625	1035		X	B	24	SB6325
MLE40, MLE60, MLW40	12	6-D100-25		13.97	1200	100	1137	28.9375	12.875	26.25	1153	X		B	24	SB6325
MLW60, MPC40, MPC60	12	6-D125-25		17.46	1500	125	1206	28.9375	12.875	31.125	1391	X		B	24	SB6325
MPE40, MPE60, MPW40	12	6-D85-25		11.87	1020	85	1040	28.9375	12.875	23.25	999	X		B	24	SB6325
MPW60, MPW65-E, MPW80	12	6-H120-25		16.76	1440	120	1206	28.9375	12.875	31.125	1377	X		B	24	SB6325
32 x 13.375 x Open	12	6-H80-25		11.17	960	80	1040	28.9375	12.875	23.25	959	X		B	24	SB6325
	12	6-P140-25		19.56	1680	140	1206	28.9375	12.875	31.125	1405	X		B	24	SB6325
	12	6-P95-25		13.27	1140	95	1040	28.9375	12.875	23.25	1009	X		B	24	SB6325
MLE40, MLE60, MLW40	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
MLW60, MPC40, MPC60	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
MPC60-E, MPC60AD	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
MPC60LD, MPE40, MPE60	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
MPE60-E, MPE80, MPE80-E	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	24	SB6325
MPW40, MPW60, MPW80	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	24	SB6325
32 x 13.375 x Open	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	24	SB6325
Max. Battery Height - 26.25"	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	24	SB6325
with rollers	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	24	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	24	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	24	SB6325
MPC80, MPE80	24	12-D100-15		16.30	700	100	3086	35.0625	12.875	26.25	1362	X		B	21	SB6325
35.75 x 13.375 x Open	24	12-D125-15		20.37	875	125	3039	35.0625	12.875	31.125	1674	X		B	21	SB6325
	24	12-D85-15		13.85	595	85	3016	35.0625	12.875	23.25	1197	X		B	21	SB6325
	24	12-H120-15		19.56	840	120	3039	35.0625	12.875	31.125	1657	X		B	21	SB6325
	24	12-H80-15		13.04	560	80	3016	35.0625	12.875	23.25	1149	X		B	21	SB6325
	24	12-P140-15		22.81	980	140	3039	35.0625	12.875	31.125	1691	X		B	21	SB6325
	24	12-P95-15		15.48	665	95	3016	35.0625	12.875	23.25	1209	X		B	21	SB6325
ME20, MS20, MS30, MS40	12	6-D85-13		5.94	510	85	1069	30.5625	7.75	22.5625	578		X	B	18	SB6325
MSB20, MSB30	12	6-H80-13		5.59	480	80	1069	30.5625	7.75	22.5625	555		X	B	18	SB6325
32.5 x 8.25 x 23.5	12	6-P95-13		6.63	570	95	1069	30.5625	7.75	22.5625	584		X	B	18	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
				KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
ME20, MS20, MS30, MS40	12	6-D85-27		12.86	1105	85	1118	31.1875	12.875	22.625	1073		X	B	18	SB6325
MSB20, MSB30	12	6-H80-27		12.11	1040	80	1118	31.1875	12.875	22.625	1030		X	B	18	SB6325
32.5 x 13.5 x 23.5	12	6-P95-27		14.38	1235	95	1118	31.1875	12.875	22.625	1084		X	B	18	SB6325
ME20, MS20, MS30, MS40	24	12-D85-11	cm	9.89	425	85	3322	31.375	12.875	22.75	939		X	B	30	SB6325
MSB20, MSB30	24	12-H80-11	cm	9.31	400	80	3322	31.375	12.875	22.75	901		X	B	30	SB6325
32.5 x 13.5 x 23.5	24	12-P95-11	cm	11.06	475	95	3322	31.375	12.875	22.75	948		X	B	30	SB6325
	24	12-D85-13		11.87	510	85	3082	30.5625	12.75	22.625	1025		X	B	18	SB6325
	24	12-H80-13		11.17	480	80	3082	30.5625	12.75	22.625	984		X	B	18	SB6325
	24	12-P95-13		13.27	570	95	3082	30.5625	12.75	22.625	1035		X	B	18	SB6325
MRW20, MRW30, MSW20	12	6-D85-15		6.93	595	85	1097	35.375	7.75	23.1875	611	X		B	20	SB6325
MSW30, MSW40	12	6-H80-15		6.52	560	80	1097	35.375	7.75	23.1875	587	X		B	20	SB6325
35.375 x 8.25 x 24	12	6-P95-15		7.74	665	95	1097	35.375	7.75	23.1875	617	X		B	20	SB6325
MRW20, MRW30, MSW20	24	12-D85-7		5.94	255	85	3198	33.5625	7.75	23.1875	598	X		B	20	SB6325
MSW30, MSW40	24	12-H80-7		5.59	240	80	3198	33.5625	7.75	23.1875	574	X		B	20	SB6325
35.375 x 8.25 x 24	24	12-P95-7		6.63	285	95	3198	33.5625	7.75	23.1875	604	X		B	20	SB6325
MRW20, MRW30, MSW20	12	6-D85-29		13.85	1190	85	1280	33.5625	12.9375	23.25	1162	X		B	20	SB6325
MSW30, MSW40	12	6-H80-29		13.04	1120	80	1280	33.5625	12.9375	23.25	1116	X		B	20	SB6325
35.375 x 13.5 x 24	12	6-P95-29		15.48	1330	95	1280	33.5625	12.9375	23.25	1174	X		B	20	SB6325
MRW20, MRW30, MSW20	24	12-D85-15		13.85	595	85	3016	35.0625	12.875	23.25	1197	X		B	20	SB6325
MSW30, MSW40	24	12-H80-15		13.04	560	80	3016	35.0625	12.875	23.25	1149	X		B	20	SB6325
35.375 x 13.5 x 24	24	12-P95-15		15.48	665	95	3016	35.0625	12.875	23.25	1209	X		B	20	SB6325
M5, M5B	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6325
32 x 8.0625 x 31.5	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6325
	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6325
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	24	SB6325
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	24	SB6325
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	24	SB6325
MCW20, MCW25, MCW30	12	6-D100-25		13.97	1200	100	1137	28.9375	12.875	26.25	1153	X		B	21	SB6325
MCW40	12	6-D85-25		11.87	1020	85	1177	28.9375	12.875	23.75	1011	X		B	21	SB6325
31.875 x 13.375 x 26.25	12	6-H80-25		11.17	960	80	1177	28.9375	12.875	23.75	971	X		B	21	SB6325
	12	6-P95-25		13.27	1140	95	1177	28.9375	12.875	23.75	1021	X		B	21	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
MCW20, MCW25, MCW30 MCW40 31.875 x 13.375 x 26.25	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	21	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	21	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	21	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	21	SB6325
MTG 28 x 13.1875 x Open	24	12-D100-11		11.64	500	100	3080	26.0625	12.75	26.25	1007	X		B	18	SB6325
	24	12-D125-11		14.55	625	125	3063	26.0625	12.75	31.125	1231	X		B	18	SB6325
	24	12-D85-11		9.89	425	85	3020	26.0625	12.75	23.25	885	X		B	18	SB6325
	24	12-H120-11		13.97	600	120	3063	26.0625	12.75	31.125	1219	X		B	18	SB6325
	24	12-H80-11		9.31	400	80	3020	26.0625	12.75	23.25	850	X		B	18	SB6325
	24	12-P140-11		16.30	700	140	3063	26.0625	12.75	31.125	1243	X		B	18	SB6325
MT, MTWR 32 x 8.0625 x 32	12	6-D100-11	cm	5.82	500	100	1167	31.25	7.75	26.1875	576	X		B	27	SB6325
	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6325
	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6325
	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6325
	12	6-D100-13		6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	18	SB6325
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	18	SB6325
	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	18	SB6325
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	18	SB6325
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	18	SB6325
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	18	SB6325
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	18	SB6325
	MT, MTW 32 x 13.375 x 25.75	12	6-D85-25		11.87	1020	85	1040	28.9375	12.875	23.25	999	X		B	18
12		6-H80-25		11.17	960	80	1040	28.9375	12.875	23.25	959	X		B	18	SB6325
12		6-P95-25		13.27	1140	95	1040	28.9375	12.875	23.25	1009	X		B	18	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
MT, MTW 32 x 13.375 x 26.25	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		B	30	SB6325
	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6325
	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6325
	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6325
	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325
MTR TUG 31.5 x 13.375 x Open	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	18	SB6325
	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	18	SB6325
	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	18	SB6325
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	18	SB6325
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	18	SB6325
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	18	SB6325
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	18	SB6325
RCL40, RCL60, RCP40 RCP60 31.75 x 8.0625 x Open	12	6-D100-11	cm	5.82	500	100	1167	31.25	7.75	26.1875	576	X		AB	27	EC5810
	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		AB	27	EC5810
	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		AB	27	EC5810
	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		AB	27	EC5810
	12	6-D100-13		6.98	600	100	1091	30.5	7.75	26.1875	613	X		AB	9	EC5810
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		AB	9	EC5810
	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		AB	9	EC5810
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		AB	9	EC5810
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		AB	9	EC5810
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		AB	9	EC5810
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		AB	9	EC5810
	RCL40, RCL60, RCP40 RCP60 31.75 x 13.5 x Open	24	12-D100-11	cm	11.64	500	100	3539	31.375	12.875	26.25	1068	X		AB	30
24		12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		AB	30	EC5810
24		12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		AB	30	EC5810
24		12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		AB	30	EC5810
24		12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		AB	9	EC5810
24		12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		AB	9	EC5810
24		12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		AB	9	EC5810
24		12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		AB	9	EC5810
24		12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		AB	9	EC5810
24		12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		AB	9	EC5810
24		12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		AB	9	EC5810

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
MCW025-E, MCW030-E	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	21	SB6329
MCW035-E	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	21	SB6329
33 x 13.5 x Open	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	21	SB6329
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	21	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	21	SB6329
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	21	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	21	SB6329
MLW040, MLW060	24	(4) 8GGC2 pm	3.60	155		3730	26	7.5	24.5	340	X		B	26	SB6325
32 x 8.125 x Open	24	12-D100-5 cm	4.66	200	100	3757	29.375	6.4375	26.1875	513	X		B	24	SB6325
	24	12-D100-5	4.66	200	100	3209	24.625	6.4375	26.1875	474	X		B	21	SB6325
	24	12-D125-5	5.82	250	125	3085	24.5625	6.5	31.0625	574	X		B	21	SB6325
	24	12-D85-5	3.96	170	85	3081	24.625	6.4375	23.1875	418	X		B	21	SB6325
	24	12-H80-5	3.72	160	80	3081	24.625	6.4375	23.1875	401	X		B	21	SB6325
	24	12-P140-5	6.52	280	140	3085	24.5625	6.5	31.0625	580	X		B	21	SB6325
	24	12-P95-5	4.42	190	95	3081	24.625	6.4375	23.1875	422	X		B	21	SB6325
MP040AC, MPB040AC	24	12-D85-5	3.96	170	85	3068	24.75	6.4375	22.5625	412		X	B	21	SB6325
28.9375 x 7.75 x 24.3125	24	12-H80-5	3.72	160	80	3068	24.75	6.4375	22.5625	396		X	B	21	SB6325
	24	12-P95-5	4.42	190	95	3068	24.75	6.4375	22.5625	416		X	B	21	SB6325
MP040AC, MPB040AC	24	12-D125-5	5.82	250	125	3201	24.625	6.5	30.4375	571		X	B	21	SB6325
25.75 x 6.9375 x Open	24	12-D85-5	3.96	170	85	3068	24.75	6.4375	22.5625	412		X	B	21	SB6325
	24	12-H80-5	3.72	160	80	3068	24.75	6.4375	22.5625	396		X	B	21	SB6325
	24	12-P140-5	6.52	280	140	3201	24.625	6.5	30.4375	577		X	B	21	SB6325
	24	12-P95-5	4.42	190	95	3068	24.75	6.4375	22.5625	416		X	B	21	SB6325
MPB040-E	24	(4) 8GGC2 pm	3.60	155		3801	25.5	7.5	24.5	340	X		B	26	SB6329
28.9375 x 8.5 x 28	24	12-D100-5	4.66	200	100	3209	24.625	6.4375	26.1875	474	X		B	16	SB6329
	24	12-D85-5	3.96	170	85	3081	24.625	6.4375	23.1875	418	X		B	16	SB6329
	24	12-H80-5	3.72	160	80	3081	24.625	6.4375	23.1875	401	X		B	16	SB6329
	24	12-P95-5	4.42	190	95	3081	24.625	6.4375	23.1875	422	X		B	16	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
MPC080, MPC080-E	24	12-D85-11	cm	9.89	425	85	3163	31.375	12.875	23.25	965	X		B	30	SB6329
MPC080AD, MPC080LD	24	12-H80-11	cm	9.31	400	80	3163	31.375	12.875	23.25	926	X		B	30	SB6329
MPE060-LE, MPE080-E	24	12-P95-11	cm	11.06	475	95	3163	31.375	12.875	23.25	975	X		B	30	SB6329
MPW060-E, MPW060-LE	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	21	SB6329
MPW080-E	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	21	SB6329
32 x 13.4375 x Open	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	21	SB6329
Max. Battery Height - 26.25	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	21	SB6329
with rollers	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	21	SB6329
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	21	SB6329
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	21	SB6329
MPE060, MPW050	12	6-D85-11	cm	4.95	425	85	1061	31.25	7.75	23.1875	516	X		B	27	SB6325
MPW065-3	12	6-H80-11	cm	4.66	400	80	1061	31.25	7.75	23.1875	495	X		B	27	SB6325
32 x 9 x Open	12	6-P95-11	cm	5.53	475	95	1061	31.25	7.75	23.1875	521	X		B	27	SB6325
	12	6-D100-13		6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	21	SB6325
	12	6-D125-13		8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	21	SB6325
	12	6-D85-13		5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	21	SB6325
	12	6-H120-13		8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	21	SB6325
	12	6-H80-13		5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	21	SB6325
	12	6-P140-13		9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	21	SB6325
	12	6-P95-13		6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	21	SB6325
MPE060, MPE060-E, MPE080	24	12-D100-7		6.98	300	100	3456	30.5	8.5625	26.1875	672	X		B	21	SB6325
MPE080-E, MPW060-E	24	12-D100-7	cm	6.98	300	100	3346	30.5	8.5625	26.1875	693	X		B	24	SB6325
MPW080	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	21	SB6325
32 x 9 x Open	24	12-D125-7		8.73	375	125	3522	31.5	8.5625	31.0625	826	X		B	21	SB6325
	24	12-D85-7		5.94	255	85	3447	30.5	8.5625	23.25	595	X		B	21	SB6325
	24	12-D85-7	cm	5.94	255	85	3415	30.5	8.5625	23.1875	606	X		B	24	SB6325
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	21	SB6325
	24	12-H120-7		8.38	360	120	3522	31.5	8.5625	31.0625	818	X		B	21	SB6325
	24	12-H80-7		5.59	240	80	3447	30.5	8.5625	23.25	571	X		B	21	SB6325
	24	12-H80-7	cm	5.59	240	80	3415	30.5	8.5625	23.1875	582	X		B	24	SB6325
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	21	SB6325
	24	12-P140-7		9.78	420	140	3522	31.5	8.5625	31.0625	834	X		B	21	SB6325
	24	12-P95-7		6.63	285	95	3447	30.5	8.5625	23.25	601	X		B	21	SB6325
	24	12-P95-7	cm	6.63	285	95	3415	30.5	8.5625	23.1875	612	X		B	24	SB6325
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	21	SB6325

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
MPW045DA 31.75 x 8.125 x Open	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	21	SB6325
	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	21	SB6325
	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	21	SB6325
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	21	SB6325
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	21	SB6325
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	21	SB6325
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	21	SB6325
MPW045-E 31.75 x 8.125 x Open	12	6-D100-13	6.98	600	100	1091	30.5	7.75	26.1875	613	X		B	21	SB6329
	12	6-D125-13	8.73	750	125	1092	30.5	7.75	31.0625	750	X		B	21	SB6329
	12	6-D85-13	5.94	510	85	1088	30.5	7.75	23.1875	538	X		B	21	SB6329
	12	6-H120-13	8.38	720	120	1092	30.5	7.75	31.0625	743	X		B	21	SB6329
	12	6-H80-13	5.59	480	80	1088	30.5	7.75	23.1875	516	X		B	21	SB6329
	12	6-P140-13	9.78	840	140	1092	30.5	7.75	31.0625	758	X		B	21	SB6329
	12	6-P95-13	6.63	570	95	1088	30.5	7.75	23.1875	543	X		B	21	SB6329
MPW045-E 28.5 x 9.125 x Open	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	21	SB6329
	24	12-D125-7	8.73	375	125	3329	25.3125	8.5625	31.0625	792	X		B	21	SB6329
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	21	SB6329
	24	12-H120-7	8.38	360	120	3329	25.3125	8.5625	31.0625	784	X		B	21	SB6329
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	21	SB6329
	24	12-P140-7	9.78	420	140	3329	25.3125	8.5625	31.0625	800	X		B	21	SB6329
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	21	SB6329
MPW050-E, MPW055-E 28 x 9.125 x Open	24	12-D100-7	6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	20	SB6329
	24	12-D125-7	8.73	375	125	3329	25.3125	8.5625	31.0625	792	X		B	20	SB6329
	24	12-D85-7	5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	20	SB6329
	24	12-H120-7	8.38	360	120	3329	25.3125	8.5625	31.0625	784	X		B	20	SB6329
	24	12-H80-7	5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	20	SB6329
	24	12-P140-7	9.78	420	140	3329	25.3125	8.5625	31.0625	800	X		B	20	SB6329
	24	12-P95-7	6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	20	SB6329
MRW020-E, MRW030-E MSW020-E, MSW030-E 33 x 13.5 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	21	SB6329
	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	21	SB6329
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	21	SB6329
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	21	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	21	SB6329
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	21	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	21	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)			
MSW020-E 27.8125 x 8.125 x Open	24	(4) 8GGC2	pm	3.60	155		3730	26	7.5	24.5	340	X		B	26	SB6329
	24	12-D100-5		4.66	200	100	3611	27.1875	6.4375	26.25	496	X		B	21	SB6329
	24	12-D85-5		3.96	170	85	3081	24.625	6.4375	23.1875	418	X		B	21	SB6329
	24	12-H80-5		3.72	160	80	3081	24.625	6.4375	23.1875	401	X		B	21	SB6329
	24	12-P95-5		4.42	190	95	3081	24.625	6.4375	23.1875	422	X		B	21	SB6329
MSW025-E 27.8125 x 9 x Open	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	21	SB6329
	24	12-D125-7		8.73	375	125	3329	25.3125	8.5625	31.0625	792	X		B	21	SB6329
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	21	SB6329
	24	12-H120-7		8.38	360	120	3329	25.3125	8.5625	31.0625	784	X		B	21	SB6329
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	21	SB6329
	24	12-P140-7		9.78	420	140	3329	25.3125	8.5625	31.0625	800	X		B	21	SB6329
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	21	SB6329
MSW030-E, MSW040-E 33 x 9 x Open	24	12-D100-7		6.98	300	100	3302	31.5	8.75	26.1875	685	X		B	21	SB6329
	24	12-D100-7	cm	6.98	300	100	3346	30.5	8.5625	26.1875	693	X		B	21	SB6329
	24	12-D100-7		6.98	300	100	3123	25.3125	8.5625	26.1875	649	X		B	21	SB6329
	24	12-D125-7		8.73	375	125	3522	31.5	8.5625	31.0625	826	X		B	21	SB6329
	24	12-D85-7		5.94	255	85	3324	31.125	8.5625	23.1875	596	X		B	21	SB6329
	24	12-D85-7	cm	5.94	255	85	3415	30.5	8.5625	23.1875	606	X		B	21	SB6329
	24	12-D85-7		5.94	255	85	3042	25.25	8.5625	23.1875	567	X		B	21	SB6329
	24	12-H120-7		8.38	360	120	3522	31.5	8.5625	31.0625	818	X		B	21	SB6329
	24	12-H80-7		5.59	240	80	3324	31.125	8.5625	23.1875	572	X		B	21	SB6329
	24	12-H80-7	cm	5.59	240	80	3415	30.5	8.5625	23.1875	582	X		B	21	SB6329
	24	12-H80-7		5.59	240	80	3042	25.25	8.5625	23.1875	544	X		B	21	SB6329
	24	12-P140-7		9.78	420	140	3522	31.5	8.5625	31.0625	834	X		B	21	SB6329
	24	12-P95-7		6.63	285	95	3324	31.125	8.5625	23.1875	602	X		B	21	SB6329
	24	12-P95-7	cm	6.63	285	95	3415	30.5	8.5625	23.1875	612	X		B	21	SB6329
	24	12-P95-7		6.63	285	95	3042	25.25	8.5625	23.1875	573	X		B	21	SB6329
MTR007-E	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	16	SB6329
MTR005-E	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	16	SB6329
31.3125 x 13.4375 x Open	24	12-D85-13		11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	16	SB6329
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	16	SB6329
	24	12-H80-13		11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	16	SB6329
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	16	SB6329
	24	12-P95-13		13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	16	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
RDF30G 39.5 x 12 x 31.25	24	12-D160-9	14.90	640	160	3007	35.062	10.937	31.125	1417	X		AB	9	EC5810
	24	12-D100-13	13.97	600	100	3212	35.5625	11.5625	26.5	1217	X		AB	9	EC5810
	24	12-D125-13	17.46	750	125	3179	35.5625	11.5625	31.125	1475	X		AB	9	EC5810
	24	12-D125-13	17.46	750	125	3260	37.6875	10.375	31.125	1468	X		AB	9	EC5810
	24	12-D85-13	11.87	510	85	3157	35.5625	11.5625	23.25	1057	X		AB	9	EC5810
	24	12-H120-13	16.76	720	120	3179	35.5625	11.5625	31.125	1460	X		AB	9	EC5810
	24	12-H120-13	16.76	720	120	3260	37.6875	10.375	31.125	1453	X		AB	9	EC5810
	24	12-H80-13	11.17	480	80	3157	35.5625	11.5625	23.25	1015	X		AB	9	EC5810
	24	12-P140-13	19.56	840	140	3179	35.5625	11.5625	31.125	1490	X		AB	9	EC5810
	24	12-P140-13	19.56	840	140	3260	37.6875	10.375	31.125	1483	X		AB	9	EC5810
	24	12-P95-13	13.27	570	95	3157	35.5625	11.5625	23.25	1068	X		AB	9	EC5810
RDF30G 39.5 x 14.5 x 31.25	24	12-D125-17	23.28	1000	125	3224	38.1875	13.5	31.1875	1975	X		AB	9	EC5810
	24	12-D85-17	15.83	680	85	3099	38.375	13.4375	23.5		X		AB	9	EC5810
	24	12-H120-17	22.35	960	120	3224	38.1875	13.5	31.1875	1955	X		AB	9	EC5810
	24	12-H80-17	14.90	640	80	3099	38.375	13.4375	23.5		X		AB	9	EC5810
	24	12-P140-17	26.07	1120	140	3224	38.1875	13.5	31.1875	1995	X		AB	9	EC5810
	24	12-P95-17	17.69	760	95	3099	38.375	13.4375	23.5		X		AB	9	EC5810
RDF30G 39.5 x 18 x 31.25	36	18-D100-15	24.44	700	100	6763	38.1875	17.8125	26.5625	2071	X		AB	9	EC5810
	36	18-D125-15	30.56	875	125	6207	38.1875	17.8125	31.1875	2542	X		AB	9	EC5810
	36	18-D85-15	20.78	595	85	6093	38.1875	17.8125	23.5625	1819	X		AB	9	EC5810
	36	18-H120-15	29.33	840	120	6207	38.1875	17.8125	31.1875	2517	X		AB	9	EC5810
	36	18-H80-15	19.56	560	80	6093	38.1875	17.8125	23.5625	1746	X		AB	9	EC5810
	36	18-P140-15	34.22	980	140	6207	38.1875	17.8125	31.1875	2567	X		AB	9	EC5810
	36	18-P95-15	23.22	665	95	6093	38.1875	17.8125	23.5625	1837	X		AB	9	EC5810
MCW025E, MCW030E MCW040E 33 x 13.5 x Open	24	12-D100-13	13.97	600	100	3493	32.5	12.75	26.25	1224	X		B	20	SB6329
MPB040E, MPW050E 28 x 9.0625 x Open	24		0.00	0		3800	25.5	8.5625	24.5	340	X		B	20	SB6329
	24	12-D85-7	5.94	255	85	3A72	27.5	8.5625	23.1875	574	X		B	20	SB6329
	24	12-H80-7	5.59	240	80	3A72	27.5	8.5625	23.1875	551	X		B	20	SB6329
	24	12-P95-7	6.63	285	95	3A72	27.5	8.5625	23.1875	580	X		B	20	SB6329
MPC060F, MPC080F MTR005F, MTR007F 31.25 x 13.4375 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6329
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6329

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
MPE060VG, MPE080VG 31.25 x 9 x Open	24	12-D100-7	6.98	300	100	3456	30.5	8.5625	26.1875	672	X		B	20	SB6329
	24	12-D85-7	5.94	255	85	3447	30.5	8.5625	23.25	595	X		B	20	SB6329
	24	12-H80-7	5.59	240	80	3447	30.5	8.5625	23.25	571	X		B	20	SB6329
	24	12-P95-7	6.63	285	95	3447	30.5	8.5625	23.25	601	X		B	20	SB6329
MPE060VG, MPE080VG 31.25 x 13.4375 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6329
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6329
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6329
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6329
MPW060E, MPW080E 32 x 9 x Open	24	12-D100-7	6.98	300	100	3456	30.5	8.5625	26.1875	672	X		B	16	SB6325
	24	12-D85-7	5.94	255	85	3324	31.125	8.5625	23.1875	596	X		B	16	SB6325
	24	12-H80-7	5.59	240	80	3324	31.125	8.5625	23.1875	572	X		B	16	SB6325
	24	12-P95-7	6.63	285	95	3324	31.125	8.5625	23.1875	602	X		B	16	SB6325
MPW060E, MPW080E 32 x 13.4375 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	16	SB6325
	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	16	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	16	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	16	SB6325

cm - Charge-Mate includes on board charger.

pm - Powr-Mate includes on board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

ORDER SELECTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

ORDER SELECTORS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
FS15, OS25, OS30 41.1875 x 14.5 x 34	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	C	30	SB6320
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	C	30	SB6320
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	C	30	SB6320
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	C	30	SB6320
	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	C	30	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	C	30	SB6320
24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	C	30	SB6320	
OS 30B Selector 3000 31.25 x 13.25 x 25.75	24	12-D100-13	13.97	600	100	3104	30.5625	12.75	25.625	1165		X	A	30	SB6320
OS 30E, OS 30EA, OS 30EB OS 30EC 36 x 13.5 x 25	24	12-D85-15	13.85	595	85	3056	35.0625	12.875	22.625	1178		X	B	16	SB6325
	24	12-H80-15	13.04	560	80	3056	35.0625	12.875	22.625	1131		X	B	16	SB6325
	24	12-P95-15	15.48	665	95	3056	35.0625	12.875	22.625	1190		X	B	16	SB6325
SS 30B 36.5 x 14.75 x Open	24	12-D160-11	18.62	800	160	3286	35.125	13.1875	31.375	1632	X		A	30	SB6320
SS 30BB 36.5 x 15.25 x Open	24	12-D125-15	20.37	875	125	3039	35.0625	12.875	31.125	1674	X		A	30	SB6320
	24	12-H120-15	19.56	840	120	3039	35.0625	12.875	31.125	1657	X		A	30	SB6320
	24	12-P140-15	22.81	980	140	3039	35.0625	12.875	31.125	1691	X		A	30	SB6320
OS 030BD, SS 030BD 39 x 14.5625 x 31.5	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	A	30	SB6320
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	A	30	SB6320
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	A	30	SB6320
OS 030BD, SS 030BD 39 x 14.5625 x 31.5	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	A	30	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	A	30	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	A	30	SB6320
OS030BC, OS030BE SS030BC, SS030BE 39 x 14.625 x 31.5	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	16	SB6322
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	16	SB6322
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	16	SB6322
OS030BD, OS030BE SS030BD, SS030BE 39 x 14.625 x 31.5	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	16	SB6322
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	16	SB6322
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	16	SB6322

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)			
NS20, NS30, NS40, NS60 38 x 12 x 31.1875	24	12-D160-9	14.90	640	160	3511	35.0625	10.9375	30.5	1309		X	B	30	SB6320	w/919
	24	12-D125-13	17.46	750	125	3176	35.5625	11.5625	30.5	1457		X	B	30	SB6320	w/919
	24	12-H120-13	16.76	720	120	3176	35.5625	11.5625	30.5	1442		X	B	30	SB6320	w/919
	24	12-P140-13	19.56	840	140	3176	35.5625	11.5625	30.5	1472		X	B	30	SB6320	w/919
NDE25, NE20, NE30, NE40 NS20, NS30, NS40, NS60 38 x 14.5 x 31.1875	24	12-D160-11	18.62	800	160	3025	35.0625	13.1875	30.5	1647		X	B	30	SB6320	w/919
	24	12-D125-15	20.37	875	125	3036	35.0625	12.875	30.5	1651		X	B	30	SB6320	w/919
	24	12-H120-15	19.56	840	120	3036	35.0625	12.875	30.5	1634		X	B	30	SB6320	w/919
	24	12-P140-15	22.81	980	140	3036	35.0625	12.875	30.5	1668		X	B	30	SB6320	w/919
NR35, NR35AC, NR35AD NR35AE, NR40A, NR40AD NR40AE, NS35, NS40A NS40AD, NS40AE, NS40AF 39 x 12.5 x 31.5	24	12-D125-15	20.37	875	125	3115	38.0625	11.875	30.5	1677		X	B	30	SB6320	w/919
	24	12-H120-15	19.56	840	120	3115	38.0625	11.875	30.5	1660		X	B	30	SB6320	w/919
	24	12-P140-15	22.81	980	140	3115	38.0625	11.875	30.5	1694		X	B	30	SB6320	w/919
NR35, NR40A, NS35, NS40A 39 x 12.5 x 31.5	36	18-D125-9	17.46	500	125	6111	38	11.0625	30.5	1504		X	B	30	SB6320	w/919
	36	18-D125-9	17.46	500	125	6063	37.6875	10.9375	30.5	1495		X	B	30	SB6320	w/919
	36	18-H120-9	16.76	480	120	6111	38	11.0625	30.5	1489		X	B	30	SB6320	w/919
	36	18-H120-9	16.76	480	120	6063	37.6875	10.9375	30.5	1480		X	B	30	SB6320	w/919
	36	18-P140-9	19.56	560	140	6111	38	11.0625	30.5	1519		X	B	30	SB6320	w/919
	36	18-P140-9	19.56	560	140	6063	37.6875	10.9375	30.5	1510		X	B	30	SB6320	w/919
NDR30A, NR35, NR40A NS35, NS40A 39 x 14 x 31.5	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	30	SB6320	w/919
	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	30	SB6320	w/919
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	30	SB6320	w/919
NDR30A, NR35, NR40A NR45, NS35, NS40A, NS50A 39 x 14 x 31.5	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	30	SB6320	w/919
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	30	SB6320	w/919
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	30	SB6320	w/919
NDE25, NE20, NE30, NE40 NS20, NS30, NS40, NS60 NSE40 38 x 17.5 x 31.8125	24	12-D160-13	22.35	960	160	3049	35.25	15.5625	30.5625	1985		X	B	30	SB6320	w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)			
NDE25, NE20, NE30, NE40	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	30	SB6320	w/919
NS20, NS30, NS40, NS60	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	30	SB6320	w/919
NSE40	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	30	SB6320	w/919
38 x 17.5 x 31.8125																
NDR30A, NR35, NR40A	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	30	SB6320	w/919
NS35, NS40A	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	30	SB6320	w/919
39 x 16.1875 x 31.5	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	30	SB6320	w/919
NDR30A, NR35, NR40A	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	30	SB6320	w/919
NS35, NS40A	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	30	SB6320	w/919
39 x 16.1875 x 31.5	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	30	SB6320	w/919
NDR30B, NR35, NR35B	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	30	SB6320	w/919
NR45B	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	30	SB6320	w/919
42 x 16.1875 x 31.5	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	30	SB6320	w/919
NDR30B, NR35, NR35B	36	18-D160-11	27.94	800	160	6644	38.9375	17.75	30.5625	2586		X	B	30	SB6320	w/919
NR45B	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	30	SB6320	w/919
42 x 18.75 x 31.5	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	30	SB6320	w/919
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	30	SB6320	w/919
NDR30B, NR35, NR35B	36	18-D160-13	33.52	960	160	6777	40.1875	20.5625	30.5625	2786		X	B	30	SB6320	w/919
NR45B	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	30	SB6320	w/919
42 x 21.0625 x 31.5	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	30	SB6320	w/919
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	30	SB6320	w/919
NDR30BC, NDR30C, NDR30CA	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	16	SB6320	
NDR30CB, NDR30G, NDR30GA	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	16	SB6320	
NDR30GB, NDR35EA, NR45C	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	16	SB6320	
NR45CA, NR45CB, NR45EA																
NR45G, NR45GA, NR45GB																
38.875 x 18.875 x 31.5																
NDR30BC, NDR30C, NDR30CB	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	16	SB6320	
NDR30G, NDR30GB, NR40G	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	16	SB6320	
NR45C, NR45CA, NR45CB	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	16	SB6320	
NR45GA, NR45GB																
38.875 x 21.0625 x 31.5																

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
NR35, NR35BC, NR45	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	30	SB6320
NR45BC, NRB	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	30	SB6320
38.875 x 18.5 x 31	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	30	SB6320
NR35, NR35BC, NR45	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	30	SB6320
NR45BC, NRB	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	30	SB6320
38.875 x 20.875 x 31	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	30	SB6320
NDR030AD, NDR030AE	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	16	SB6320
NDR030DA, NR035AC	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	16	SB6320
NR035AD, NR035AE	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	16	SB6320
NR040AC, NR040AD															
NR040AE, NS040AD															
NS040AF															
39 x 14.5 x 31.5															
NDR030AD, NDR030AE	36	18-D125-11	21.83	625	125	6782	38.0625	13.5625	30.5625	1887		X	B	16	SB6320
NDR030DA, NR030EA	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	16	SB6320
NR035AC, NR035AD	36	18-H120-11	20.95	600	120	6782	38.0625	13.5625	30.5625	1868		X	B	16	SB6320
NR035AE, NR035EA	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	16	SB6320
NR040AC, NR040AD	36	18-P140-11	24.44	700	140	6782	38.0625	13.5625	30.5625	1906		X	B	16	SB6320
NR040AE, NR040EA	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	16	SB6320
NR045AC, NR045AD															
NR045AE, NS040AD															
NS040AF, NS050AD															
NS050AF															
39 x 14.5 x 31.5															
NDR030AD, NDR030AE	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	16	SB6320
NR035AC, NR035AD	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	16	SB6320
NR035AE, NR040AC	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	16	SB6320
NR040AD, NR040AE															
NS040AD, NS040AF															
39 x 16.5 x 31.5															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
NDR030AD, NDR030AE	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	16	SB6320
NDR030DA, NDR030EA	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	16	SB6320
NDR035EA, NR035AC	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	16	SB6320
NR035AD, NR035AE															
NR035EA, NR040AC															
NR040AD, NR040AE															
NR040EA, NR045AC															
NR045AD, NR045AE															
NR045EA, NS040AF															
NS050AF															
39 x 16.5 x 31.5															
NS040AE	24	12-D125-17	23.28	1000	125	3127	38.1875	13.5	30.5625	1944		X	B	30	SB6320
38.9375 x 14.625 x 31.5	24	12-H120-17	22.35	960	120	3127	38.1875	13.5	30.5625	1925		X	B	30	SB6320
	24	12-P140-17	26.07	1120	140	3127	38.1875	13.5	30.5625	1963		X	B	30	SB6320
NS040AE	24	12-D125-19	26.19	1125	125	3134	38.1875	15	30.5625	2126		X	B	30	SB6320
38.9375 x 16.625 x 31.5	24	12-H120-19	25.14	1080	120	3134	38.1875	15	30.5625	2105		X	B	30	SB6320
	24	12-P140-19	29.33	1260	140	3134	38.1875	15	30.5625	2147		X	B	30	SB6320
NS040AE, NS050AE	36	18-D125-11	21.83	625	125	6782	38.0625	13.5625	30.5625	1887		X	B	30	SB6320
38.9375 x 14.625 x 31.5	36	18-D125-11	21.83	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	30	SB6320
	36	18-H120-11	20.95	600	120	6782	38.0625	13.5625	30.5625	1868		X	B	30	SB6320
	36	18-H120-11	20.95	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	30	SB6320
	36	18-P140-11	24.44	700	140	6782	38.0625	13.5625	30.5625	1906		X	B	30	SB6320
	36	18-P140-11	24.44	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	30	SB6320
NS040AE, NS050AE	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	30	SB6320
38.9375 x 16.625 x 31.5	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	30	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	30	SB6320
NDR030DA	24	12-D125-15	20.37	875	125	3115	38.0625	11.875	30.5	1677		X	B	16	SB6322
39 x 12.5 x 31.5	24	12-H120-15	19.56	840	120	3115	38.0625	11.875	30.5	1660		X	B	16	SB6322
	24	12-P140-15	22.81	980	140	3115	38.0625	11.875	30.5	1694		X	B	16	SB6322
NDR035EA	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	16	SB6320
39 x 18.5 x 31.5	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	16	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	16	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STRADDLE, STRADDLE REACH TRUCKS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
NDR035EA 39 x 21.5 x 31.5	36	18-D125-17	34.92	1000	125	6056	38.5	21	30.5625	2887		X	B	16	SB6320
	36	18-H120-17	33.52	960	120	6056	38.5	21	30.5625	2858		X	B	16	SB6320
	36	18-P140-17	39.11	1120	140	6056	38.5	21	30.5625	2916		X	B	16	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

TURRET TRUCK

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
NTD22A, NTD33B, NTD33D NTD44E 51.1875 x 30.6875 x 33.875 See Note A												X	B	40	SBX6343
NTU22CK, NTU26AK, NTU30C NTU33AB 42.875 x 28.875 x 40.375 See Note B	80	20-D125-9 sp	19.40 ea	500	125	9049	25.3125	19.25	34	1710		X	B	40	SBX6343
	80	20-H120-9 sp	18.62 ea	480	120	9049	25.3125	19.25	34	1693		X	B	40	SBX6343
	80	20-P140-9 sp	21.73 ea	560	140	9049	25.3125	19.25	34	1727		X	B	40	SBX6343
NTU26BK, NTU33B 42.875 x 33.25 x 40.375 See Note C												X	B	40	SBX6343
NTA30SA 44.375 x 21.25 x 32.25	48	24-D125-13	34.92	750	125	7195	44	20.5625	30.5625	3042		X	C	12	SB6321
	48	24-H120-13	33.52	720	120	7195	44	20.5625	30.5625	3012		X	C	12	SB6321
	48	24-P140-13	39.11	840	140	7195	44	20.5625	30.5625	3072		X	C	12	SB6321

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET TRUCK (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
NTA40SA 40.375 x 27.8125 x 34.375	72	36-D125-11	43.65	625	125	8060	37.8125	26.1875	30.5625	3618		X	C	12	SB6320
	72	36-H120-11	41.90	600	120	8060	37.8125	26.1875	30.5625	3582		X	C	12	SB6320
	72	36-P140-11	48.89	700	140	8060	37.8125	26.1875	30.5625	3654		X	C	12	SB6320
NTA40DA 46.125 x 37.5625 x 33.25 See Note D												X	C	12	SB6320
NTA030SB 38.75 x 23.625 x 31	48	24-D125-15	40.74	875	125	7014	38.1875	23.5625	30.5625	3268		X	B	30	SB6321
	48	24-H120-15	39.11	840	120	7014	38.1875	23.5625	30.5625	3235		X	B	30	SB6321
	48	24-P140-15	45.63	980	140	7014	38.1875	23.5625	30.5625	3301		X	B	30	SB6321
NTA030SB 38.75 x 23.8125 x 31	48	24-D125-15	40.74	875	125	7014	38.1875	23.5625	30.5625	3268		X	B	30	SB6321
	48	24-H120-15	39.11	840	120	7014	38.1875	23.5625	30.5625	3235		X	B	30	SB6321
	48	24-P140-15	45.63	980	140	7014	38.1875	23.5625	30.5625	3301		X	B	30	SB6321
NTA030SB 38.4375 x 26.8125 x 31	48	24-D125-17	46.56	1000	125	7024	38.1875	26.6875	30.5625	3770		X	B	30	SB6321
	48	24-H120-17	44.70	960	120	7024	38.1875	26.6875	30.5625	3732		X	B	30	SB6321
	48	24-P140-17	52.15	1120	140	7024	38.1875	26.6875	30.5625	3808		X	B	30	SB6321
NTA030SB 38.75 x 27 x 31	48	24-D125-17	46.56	1000	125	7024	38.1875	26.6875	30.5625	3770		X	B	30	SB6321
	48	24-H120-17	44.70	960	120	7024	38.1875	26.6875	30.5625	3732		X	B	30	SB6321
	48	24-P140-17	52.15	1120	140	7024	38.1875	26.6875	30.5625	3808		X	B	30	SB6321
NTA030SB 44.25 x 20.8125 x 31 Min. Battery Wt. - 2976 lbs.	48	24-D125-13	34.92	750	125	7195	44	20.5625	30.5625	3042		X	B	30	SB6321
	48	24-H120-13	33.52	720	120	7195	44	20.5625	30.5625	3012		X	B	30	SB6321
	48	24-P140-13	39.11	840	140	7195	44	20.5625	30.5625	3072		X	B	30	SB6321
NTA035SB 38.3125 x 17.9375 x 31 See Note H	72	18-D125-15	30.56 ea	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	30	SB6324
	72	18-H120-15	29.33 ea	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	30	SB6324
	72	18-P140-15	34.22 ea	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	30	SB6324
NTA035SB 38.3125 x 20.125 x 31 See Note H	72	18-D125-17	34.92 ea	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	30	SB6324
	72	18-H120-17	33.52 ea	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	30	SB6324
	72	18-P140-17	39.11 ea	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	30	SB6324
NTA035SB 38.3125 x 20.4375 x 31 See Note H	72	18-D125-17	34.92 ea	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	30	SB6324
	72	18-H120-17	33.52 ea	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	30	SB6324
	72	18-P140-17	39.11 ea	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	30	SB6324

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET TRUCK (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
NTA035SB 37.9375 x 15.5 x 31 See Note H	72	18-D125-11	21.83 ea	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	30	SB6324
	72	18-H120-11	20.95 ea	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	30	SB6324
	72	18-P140-11	24.44 ea	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	30	SB6324
NTA035SB 38.125 x 15.8125 x 31 See Note H	72	18-D125-9	17.46 ea	500	125	6816	38	11	30.875	1524		X	B	30	SB6324
	72	18-H120-9	16.76 ea	480	120	6816	38	11	30.875	1509		X	B	30	SB6324
	72	18-P140-9	19.56 ea	560	140	6816	38	11	30.875	1539		X	B	30	SB6324
NTA035SB 38.3125 x 13.5 x 31 See Note H	72	18-D125-11	21.83 ea	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	30	SB6324
	72	18-H120-11	20.95 ea	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	30	SB6324
	72	18-P140-11	24.44 ea	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	30	SB6324
NTA035SB 37.9375 x 14 x 31 See Note H	72	18-D125-11	21.83 ea	625	125	6016	37.8125	13.3125	30.5625	1848		X	B	30	SB6324
	72	18-H120-11	20.95 ea	600	120	6016	37.8125	13.3125	30.5625	1830		X	B	30	SB6324
	72	18-P140-11	24.44 ea	700	140	6016	37.8125	13.3125	30.5625	1866		X	B	30	SB6324
NTA035SB 37.9375 x 26.75 x 31 See Note H	72	18-D125-17	34.92 ea	1000	125	6284	31.9375	26.6875	30.5625	904		X	B	30	SB6324
	72	18-H120-17	33.52 ea	960	120	6284	31.9375	26.6875	30.5625	895		X	B	30	SB6324
	72	18-P140-17	39.11 ea	1120	140	6284	31.9375	26.6875	30.5625	913		X	B	30	SB6324

Note A - Contact EPM factory for new special battery tray design for 20-D160-9 (43.69 x 14.44 x 34). Requires two 20 cell, 40 volt batteries wired in series for 80 volt system.

Note B - These truck models require two (2) 20 cell, 40 volt batteries.

Note C - Contact EPM factory for new special battery tray design for 20-D125-13 (31.5 x 20.44 x 34). Requires two 20 cell, 40 volt batteries wired in series for 80 volt system.

Note D - Contact EPM factory for new special battery tray design for 36-D125-15 (38.19 x 35.19 x 30.5) 72 volt system.

Note H - These truck models require two (2) 18 cell, 36 volt batteries.

Sp - Special tray IST9049 includes channels welded to bottom.

ea - KWH calculated for each 20 cell battery.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

STAND-UP RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
ESC20A, ESC20AB, ESC25A	24	12-D125-15	20.37	875	125	3039	35.0625	12.875	31.125	1674	X		B	21	SB6320 w/919
ESC25AB, ESC30A, ESC30AB	24	12-H120-15	19.56	840	120	3039	35.0625	12.875	31.125	1657	X		B	21	SB6320 w/919
36.5 x 13.5625 x 31.25	24	12-P140-15	22.81	980	140	3039	35.0625	12.875	31.125	1691	X		B	21	SB6320 w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)			
ESC20H, ESC30H 33.5 x 26.5 x 24.375	36	18-D85-15	20.78	595	85	6043	32	23.5625	23.5625	1857	X		A	30	SB6320	w/919
	36	18-H80-15	19.56	560	80	6043	32	23.5625	23.5625	1783	X		A	30	SB6320	w/919
	36	18-P95-15	23.22	665	95	6043	32	23.5625	23.5625	1876	X		A	30	SB6320	w/919
ESC30HC 39 x 16 x Open	36	18-D125-13	26.19	750	125	6277	37.8125	15.5625	31.1875	2199	X		B	24	SB6320	w/919
	36	18-H120-13	25.14	720	120	6277	37.8125	15.5625	31.1875	2177	X		B	24	SB6320	w/919
	36	18-P140-13	29.33	840	140	6277	37.8125	15.5625	31.1875	2221	X		B	24	SB6320	w/919
ESC40HC 39 x 20.75 x Open	36	18-D85-17	23.75	680	85	6059	38.1875	20.0625	23.5625	2096	X		B	24	SB6320	w/919
	36	18-H80-17	22.35	640	80	6059	38.1875	20.0625	23.5625	2012	X		B	24	SB6320	w/919
	36	18-P95-17	26.54	760	95	6059	38.1875	20.0625	23.5625	2117	X		B	24	SB6320	w/919
ESC30ZA, ESC35ZA 38.75 x 16.125 x 31.5 Min. Battery Wt. - 1925 lbs.	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	D	9	SB6320	
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	D	9	SB6320	
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	D	9	SB6320	
ESC30ZA, ESC35ZA 38.6875 x 18.125 x 31.5 Min. Battery Wt. - 2175 lbs.	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	D	9	SB6320	
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	D	9	SB6320	
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	D	9	SB6320	
ESC40ZA, ESC50ZA 38.875 x 20.75 x 31.5 Min. Battery Wt. - 2700 lbs.	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	D	9	SB6320	
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	D	9	SB6320	
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	D	9	SB6320	
ESC020AB, ESC025AB ESC030AB 36.5 x 13.625 x 31.3125	36	18-D125-9	17.46	500	125	6289	32.0625	12.75	31.125	1505	X		B	21	SB6320	
	36	18-H120-9	16.76	480	120	6289	32.0625	12.75	31.125	1490	X		B	21	SB6320	
	36	18-P140-9	19.56	560	140	6289	32.0625	12.75	31.125	1520	X		B	21	SB6320	
ESC030EA 38.75 x 16.125 x 31.5	36	18-D125-13	26.19	750	125	6512	38.125	15.5625	31.1875	2250	X		D	9	SB6320	
	36	18-H120-13	25.14	720	120	6512	38.125	15.5625	31.1875	2228	X		D	9	SB6320	
	36	18-P140-13	29.33	840	140	6512	38.125	15.5625	31.1875	2273	X		D	9	SB6320	
ESC030FA 38.625 x 16.3125 x 31.125	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	D	9	SB6320	
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	D	9	SB6320	
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	D	9	SB6320	
ESC030FA, ESC035FA 38.625 x 18.3125 x 31.125	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	D	9	SB6320	
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	D	9	SB6320	
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	D	9	SB6320	

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
ESC035FA, ESC040FA 38.625 x 20.8125 x 31.125	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	D	9	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	D	9	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	D	9	SB6320
ESC030AC 38.5625 x 16.25 x 31.0625	36	18-D125-13	26.19	750	125	6005	37.8125	15.5625	30.5625	2168		X	B	16	SB6320
	36	18-H120-13	25.14	720	120	6005	37.8125	15.5625	30.5625	2146		X	B	16	SB6320
	36	18-P140-13	29.33	840	140	6005	37.8125	15.5625	30.5625	2190		X	B	16	SB6320
ESC030AC, ESC035AC 38.5625 x 18.25 x 31.0625	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	16	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	16	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	16	SB6320
ESC035AC 38.5625 x 20.75 x 31.0625	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	16	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	16	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	16	SB6320
ESC040AC 38.5625 x 18.25 x 31.0625	36	18-D125-15	30.56	875	125	6045	38.1875	17.8125	30.5625	2486		X	B	25	SB6320
	36	18-H120-15	29.33	840	120	6045	38.1875	17.8125	30.5625	2461		X	B	25	SB6320
	36	18-P140-15	34.22	980	140	6045	38.1875	17.8125	30.5625	2511		X	B	25	SB6320
ESC040AC 38.5625 x 20.75 x 31.0625	36	18-D125-17	34.92	1000	125	6069	38.1875	20.0625	30.5625	2834		X	B	25	SB6320
	36	18-H120-17	33.52	960	120	6069	38.1875	20.0625	30.5625	2806		X	B	25	SB6320
	36	18-P140-17	39.11	1120	140	6069	38.1875	20.0625	30.5625	2862		X	B	25	SB6320

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

SIT DOWN RIDERS

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
ERC20T, ERC25T, ERC30T 35 x 19.8125 x 24	24	12-D85-21	19.79	850	85	3078	32.5625	19.1875	22.625	1638		X	B	20	SB6320 w/919
	24	12-H80-21	18.62	800	80	3078	32.5625	19.1875	22.625	1572		X	B	20	SB6320 w/919
	24	12-P95-21	22.12	950	95	3078	32.5625	19.1875	22.625	1654		X	B	20	SB6320 w/919
ERP, ERC30T 38.875 x 17.5 x 26 See Note E	24	12-D100-21	23.28	1000	100	3139	38.1875	16.5	25.6875	1910		X	B	20	SB6320 w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos. (in.)	Length (in.)		
ERP, ERC35T 38.875 x 21.875 x 26 See Note E	24	12-D100-25	27.94	1200	100	3105	38.1875	19.5	25.6875	2255		X	B	30	SB6320	w/919
ERP30TD, ERP30TF ERP30TG, ERP30TH 39 x 21 x 26.75 See Note F	36	18-D100-17	27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	B	30	SB6320	w/919
ERP30TD, ERP30TF ERP30TG, ERP30TH 39 x 21 x 26.75 See Note G	48	24-D100-13	27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	B	30	SB6320	w/919
	48	24-D85-13	23.75	510	85	7017	37.8125	20.5625	22.6875	2030		X	B	30	SB6320	w/919
	48	24-H80-13	22.35	480	80	7017	37.8125	20.5625	22.6875	1949		X	B	30	SB6320	w/919
	48	24-P95-13	26.54	570	95	7017	37.8125	20.5625	22.6875	2050		X	B	30	SB6320	w/919
ERP35TD, ERP35TF ERP35TG, ERP40TD ERP40TF, ERP40TG 39 x 25 x 26.75 See Note F	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	B	30	SB6320	w/919
	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	30	SB6320	w/919
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	30	SB6320	w/919
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	30	SB6320	w/919
ERP35TD, ERP35TF ERP35TG, ERP40TD ERP40TF, ERP40TG 39 x 25 x 26.75 See Note G	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	30	SB6320	w/919
	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	B	30	SB6320	w/919
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	B	30	SB6320	w/919
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	B	30	SB6320	w/919
ERC25A, ERC30A, ERC35A ERC40A, ERP25A, ERP30A 35 x 26.5 x 23.0625	36	18-D85-17	23.75	680	85	6001	33.1875	25.5625	22.6875	2090		X	B	30	SB6320	w/919
	36	18-H80-17	22.35	640	80	6001	33.1875	25.5625	22.6875	2006		X	B	30	SB6320	w/919
	36	18-P95-17	26.54	760	95	6001	33.1875	25.5625	22.6875	2111		X	B	30	SB6320	w/919
ERC25A, ERC30A, ERC35A ERC40A, ERP25A, ERP30A 35 x 26.5 x 23.0625	48	24-D85-13	23.75	510	85	7007	30.6875	25.3125	22.6875	2033		X	B	30	SB6320	w/919
	48	24-H80-13	22.35	480	80	7007	30.6875	25.3125	22.6875	1952		X	B	30	SB6320	w/919
	48	24-P95-13	26.54	570	95	7007	30.6875	25.3125	22.6875	2053		X	B	30	SB6320	w/919
ERC30B, ERC30BC, ERC35B ERC40B, ERC40BC, ERP30B ERP35B, ERP40B 39.25 x 27.6875 x 23	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	30	SB6320	w/919
	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	30	SB6320	w/919
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	30	SB6320	w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
ERC30B, ERC30BC, ERC35B	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	30	SB6320	w/919
ERC40B, ERC40BC, ERP30B	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	30	SB6320	w/919
ERP35B, ERP40B 39.25 x 27.6875 x 23	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	30	SB6320	w/919
ERP40R, ERP50R 42.5 x 39 x 24	36	18-D85-33	47.49	1360	85	6121	38.1875	38.1875	23.5625	4002	X		B	10	SB6320	w/919
	36	18-H80-33	44.70	1280	80	6121	38.1875	38.1875	23.5625	3842	X		B	10	SB6320	w/919
	36	18-P95-33	53.08	1520	95	6121	38.1875	38.1875	23.5625	4042	X		B	10	SB6320	w/919
ERP40R, ERP50R 42.5 x 39 x 24	48	24-D85-27	51.45	1105	85	7047	41.6875	38.1875	23.5625	4218	X		B	10	SB6320	w/919
	48	24-H80-27	48.42	1040	80	7047	41.6875	38.1875	23.5625	4049	X		B	10	SB6320	w/919
	48	24-P95-27	57.50	1235	95	7047	41.6875	38.1875	23.5625	4260	X		B	10	SB6320	w/919
ERP40R, ERP50R 42.5 x 39 x 24 See Note H	72	18-D85-17	23.75 ea	680	85	6C55	39.6875	19.3125	23.3125	2054	X		D	20	SB6320	w/919
	72	18-H80-17	22.35 ea	640	80	6C55	39.6875	19.3125	23.3125	1972	X		D	20	SB6320	w/919
	72	18-P95-17	26.54 ea	760	95	6C55	39.6875	19.3125	23.3125	2075	X		D	20	SB6320	w/919
ERP60R 44.75 x 42.5 x 24 See Note I	36	36-D85-19	53.43	1530	85	8006	44.1875	38.1875	23.5625	4438	X		B	10	SB6320	w/919
	36	36-H80-19	50.28	1530	80	8006	44.1875	38.1875	23.5625	4260	X		B	10	SB6320	w/919
	36	36-P95-19	59.71	1530	95	8006	44.1875	38.1875	23.5625	4482	X		B	10	SB6320	w/919
ERP60R 44.75 x 42.5 x 24	48	24-D85-27	** 51.45	1105	85	7554	41.6875	38.1875	23.5625	4217	X		B	10	SB6320	w/919
	48	24-D85-27	51.45	1105	85	7047	41.6875	38.1875	23.5625	4218	X		B	10	SB6320	w/919
	48	24-H80-27	** 48.42	1040	80	7554	41.6875	38.1875	23.5625	4048	X		B	10	SB6320	w/919
	48	24-H80-27	48.42	1040	80	7047	41.6875	38.1875	23.5625	4049	X		B	10	SB6320	w/919
	48	24-P95-27	** 57.50	1235	95	7554	41.6875	38.1875	23.5625	4259	X		B	10	SB6320	w/919
	48	24-P95-27	57.50	1235	95	7047	41.6875	38.1875	23.5625	4260	X		B	10	SB6320	w/919
ERP60R 44.75 x 42.5 x 24 See Note H	72	18-D85-19	26.71 ea	765	85	6037	38.1875	22.3125	23.5625	2310	X		D	20	SB6320	w/919
	72	18-H80-19	25.14 ea	720	80	6037	38.1875	22.3125	23.5625	2218	X		D	20	SB6320	w/919
	72	18-P95-19	29.86 ea	855	95	6037	38.1875	22.3125	23.5625	2333	X		D	20	SB6320	w/919
ERC40J, ERC50J 39.5 x 30.5625 x 24	36	18-D85-25	35.62	1020	85	6008	38.1875	29.1875	23.5625	2996	X		B	30	SB6320	w/919
	36	18-H80-25	33.52	960	80	6008	38.1875	29.1875	23.5625	2876	X		B	30	SB6320	w/919
	36	18-P95-25	39.81	1140	95	6008	38.1875	29.1875	23.5625	3026	X		B	30	SB6320	w/919
ERC40J, ERC50J 39.5 x 30.5625 x 24	48	24-D85-19	35.62	765	85	7010	38.1875	29.6875	23.5625	3068	X		B	30	SB6320	w/919
	48	24-H80-19	33.52	720	80	7010	38.1875	29.6875	23.5625	2945	X		B	30	SB6320	w/919
	48	24-P95-19	39.81	855	95	7010	38.1875	29.6875	23.5625	3099	X		B	30	SB6320	w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.		
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)			
ERC40F, ERC50F, ERC60F 39.0625 x 33.5625 x 23	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	30	SB6320	w/919	
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	30	SB6320	w/919	
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	30	SB6320	w/919	
ERC40F, ERC59F, ERC60F 39.0625 x 33.5625 x 23	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	30	SB6320	w/919	
	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	30	SB6320	w/919	
	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	30	SB6320	w/919	
ERC040, ERC040GH ERC040RA, ERC040RF ERC040RG, ERC040ZF ERC040ZG, ERC050 ERC050GH, ERC050RA ERC050RF, ERC050RG 38.8125 x 30.75 x 24.375	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	30	SB6320		
	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	30	SB6320		
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	30	SB6320		
ERC040, ERC040GH ERC040RA, ERC040RF ERC040RG, ERC040ZF ERC040ZG, ERC050 ERC050GH, ERC050RA ERC050RF, ERC050RG 38.8125 x 30.75 x 24.375	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	30	SB6321		
	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	30	SB6321		
	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	30	SB6321		
ERC040RF, ERC040GH ERC040RG, ERC040ZF ERC040ZG, ERC050GH ERC050RF, ERC050RG ERC050ZF, ERC050ZG ERC060GH, ERC060RA ERC060RF, ERC060RG ERC060ZG Optional Compartment 38.8125 x 33.125 x 24.375	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	30	SB6320		
	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	30	SB6320		
	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	30	SB6320		

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
ERC040RF, ERC040GH	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	30	SB6321
ERC040RG, ERC040ZF	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	30	SB6321
ERC040ZG, ERC050GH	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	30	SB6321
ERC050RF, ERC050RG ERC050ZG, ERC060GH ERC060RA, ERC060RF ERC060RG, ERC060ZG Optional Compartment 38.8125 x 33.125 x 24.375															
ERC040RF, ERC040	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	30	SB6320
ERC040GH, ERC040RG	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	30	SB6320
ERC040ZF, ERC040ZG	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	30	SB6320
ERC050, ERC050GH ERC050RA, ERC050RF ERC050RG, ERC050ZF ERC050ZG Optional Compartment 38.8125 x 27.3125 x 24.375															
ERC040RF, ERC040	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	30	SB6321
ERC040GH, ERC040RA	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	30	SB6321
ERC040RG, ERC040ZF	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	30	SB6321
ERC040ZG, ERC050 ERC050GH, ERC050RA ERC050RF, ERC050RG ERC050ZF, ERC050ZG Optional Compartment 38.8125 x 27.3125 x 24.375															
ERC050ZF, ERC050ZG	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	30	SB6320
Optional Compartment	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	30	SB6320
38.8125 x 30.75 x 24.375	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	30	SB6320
ERC050ZF, ERC050ZG	48	24-D85-19	35.62	765	85	7003	38.1875	29.6875	22.6875	2984		X	B	30	SB6321
Optional Compartment	48	24-H80-19	33.52	720	80	7003	38.1875	29.6875	22.6875	2865		X	B	30	SB6321
38.8125 x 30.75 x 24.375	48	24-P95-19	39.81	855	95	7003	38.1875	29.6875	22.6875	3014		X	B	30	SB6321
ERC60H, ERC70H	36	18-D100-27	45.40	1300	100	6281	38.1875	31.4375	25.6875	3608		X	B	30	SB6320 w/919
39.0625 x 33.5625 x 26															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)		
ERC60H, ERC70H 39.0625 x 33.5625 x 26	48	24-D100-21	46.56	1000	100	7117	38.1875	32.6875	25.6875	3754		X	B	30	SB6320	w/919
ERC100H, ERC80H 39.0625 x 39.0625 x 26	36	18-D100-33	55.87	1600	100	6081	38.1875	38.1875	25.6875	4323		X	B	30	SB6320	w/919
ERC100H, ERC80H 39.0625 x 39.0625 x 26	48	24-D100-25	55.87	1200	100	7061	38.6875	38.1875	25.6875	4465		X	B	30	SB6320	w/919
ERC120H 43.0625 x 40.5 x 26	36	18-D100-33	55.87	1600	100	6081	38.1875	38.1875	25.6875	4323		X	B	30	SB6320	w/919
ERC120H 43.0625 x 40.5 x 26	48	24-D100-25	55.87	1200	100	7061	38.6875	38.1875	25.6875	4465		X	B	30	SB6320	w/919
ERC070HG, ERC070HH ERC080HG, ERC080HH ERC100HD, ERC100HG ERC100HH, ERC70HD ERC80HD 44.0625 x 39.125 x 23.125	36	18-D85-33	47.49	1360	85	6065	38.1875	38.1875	22.6875	3887		X	B	30	SB6320	w/919
	36	18-H80-33	44.70	1280	80	6065	38.1875	38.1875	22.6875	3732		X	B	30	SB6320	w/919
	36	18-P95-33	53.08	1520	95	6065	38.1875	38.1875	22.6875	3926		X	B	30	SB6320	w/919
ERC070HG, ERC070HH ERC080HG, ERC080HH ERC100HD, ERC100HG ERC100HH, ERC70HD ERC80HD 44.0625 x 39.125 x 23.125	48	24-D85-27	51.45	1105	85	7085	41.6875	38.1875	22.6875	4097		X	B	30	SB6320	w/919
	48	24-H80-27	48.42	1040	80	7085	41.6875	38.1875	22.6875	3933		X	B	30	SB6320	w/919
	48	24-P95-27	57.50	1235	95	7085	41.6875	38.1875	22.6875	4138		X	B	30	SB6320	w/919
ERC100HD, ERC100HG ERC100HH 45.6875 x 44.6875 x 23.125 Optional Compartment See Note I	36	36-D85-21	59.36	1700	85	8059	43.5	43.5	22.6875	4909		X	B	30	SB6320	w/919
	36	36-H80-21	55.87	1700	80	8059	43.5	43.5	22.6875	4713		X	B	30	SB6320	w/919
	36	36-P95-21	66.35	1700	95	8059	43.5	43.5	22.6875	4958		X	B	30	SB6320	w/919
ERC100HD, ERC100HG ERC100HH 45.6875 x 44.6875 x 23.125	48	24-D85-29	55.41	1190	85	7067	44.6875	38.1875	22.6875	4497		X	B	30	SB6320	w/919
	48	24-H80-29	52.15	1120	80	7067	44.6875	38.1875	22.6875	4317		X	B	30	SB6320	w/919
	48	24-P95-29	61.92	1330	95	7067	44.6875	38.1875	22.6875	4542		X	B	30	SB6320	w/919

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)			
ERC120HD, ERC120HG	36	36-D85-21	59.36	1700	85	8038	43.625	43.625	22.75	5010		X	B	30	SB6320	w/919
ERC120HH	36	36-H80-21	55.87	1700	80	8038	43.625	43.625	22.75	4810		X	B	30	SB6320	w/919
45.6875 x 44.6875 x 23.125 See Note I	36	36-P95-21	66.35	1700	95	8038	43.625	43.625	22.75	5060		X	B	30	SB6320	w/919
ERC120HD, ERC120HG	48	24-D85-29	55.41	1190	85	7067	44.6875	38.1875	22.6875	4497		X	B	30	SB6320	w/919
ERC120HH	48	24-H80-29	52.15	1120	80	7067	44.6875	38.1875	22.6875	4317		X	B	30	SB6320	w/919
45.6875 x 44.6875 x 23.125	48	24-P95-29	61.92	1330	95	7067	44.6875	38.1875	22.6875	4542		X	B	30	SB6320	w/919
ERC120K, ERC140K	72	18-D85-19	26.71 ea	765	85	6037	38.1875	22.3125	23.5625	2310	X		C	30	SB6320	
ERC150K	72	18-H80-19	25.14 ea	720	80	6037	38.1875	22.3125	23.5625	2218	X		C	30	SB6320	
47 x 40 x 24 See Note H	72	18-P95-19	29.86 ea	855	95	6037	38.1875	22.3125	23.5625	2333	X		C	30	SB6320	
ERC050ZF, ERC050ZG	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	30	SB6320	
ERC060RF, ERC060RG	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	30	SB6320	
ERC060ZF, ERC060ZG 38.8125 x 33.125 x 24.375	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	30	SB6320	
ERC050ZF, ERC050ZG	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	30	SB6321	
ERC060RF, ERC060RG	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	30	SB6321	
ERC060ZF, ERC060ZG 38.8125 x 33.125 x 24.375	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	30	SB6321	
ERC065GH, ERC065RF	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3603		X	B	30	SB6320	
ERC065RG, ERC065ZF	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3459		X	B	30	SB6320	
ERC065ZG 38.8125 x 36.5 x 24.375	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3639		X	B	30	SB6320	
ERC065GH, ERC065RF	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573		X	B	30	SB6321	
ERC065RG, ERC065ZF	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430		X	B	30	SB6321	
ERC065ZG 38.8125 x 36.5 x 24.375	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609		X	B	30	SB6321	
ERC030AF, ERC030AG	36	18-D85-17	23.75	680	85	6001	33.1875	25.5625	22.6875	2090		X	B	30	SB6320	
ERC030AH, ERC030BG	36	18-H80-17	22.35	640	80	6001	33.1875	25.5625	22.6875	2006		X	B	30	SB6320	
ERC040AF, ERC040AG	36	18-P95-17	26.54	760	95	6001	33.1875	25.5625	22.6875	2111		X	B	30	SB6320	
ERC040AH, ERC040BG 34.5625 x 27.3125 x 24.25																

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
ERC030AF, ERC030AG	48	24-D85-13	23.75	510	85	7007	30.6875	25.3125	22.6875	2033		X	B	30	SB6321
ERC030AH, ERC030BG	48	24-H80-13	22.35	480	80	7007	30.6875	25.3125	22.6875	1952		X	B	30	SB6321
ERC040AF, ERC040AG	48	24-P95-13	26.54	570	95	7007	30.6875	25.3125	22.6875	2053		X	B	30	SB6321
ERC040AH, ERC040BG 34.5625 x 27.3125 x 24.25															
ERC030AF, ERC030AG	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	30	SB6320
ERC030AH, ERC030BG	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	30	SB6320
ERC040AF, ERC040AG	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	30	SB6320
ERC040AH, ERC040BG 35.75 x 27.3125 x 24.25															
ERC030AF, ERC030AG	48	24-D85-15	27.70	595	85	7049	35.1875	25.5625	22.6875	2332		X	B	30	SB6321
ERC030AH, ERC030BG	48	24-H80-15	26.07	560	80	7049	35.1875	25.5625	22.6875	2239		X	B	30	SB6321
ERC040AF, ERC040AG	48	24-P95-15	30.96	665	95	7049	35.1875	25.5625	22.6875	2355		X	B	30	SB6321
ERC040AH, ERC040BG 35.75 x 27.3125 x 24.25															
ERP035TH with rollers	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	A	21	SB6320
ERP040TH with rollers	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	A	21	SB6320
39 x 25 x 23.125	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	A	21	SB6320
See Note F															
ERP035TH without rollers	36	18-D100-21	34.92	1000	100	6067	38.1875	24.5625	25.6875	2805		X	A	21	SB6320
ERP040TH without rollers															
39 x 25 x 26.125															
See Note F															
ERP035TH with rollers	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	A	21	SB6321
ERP040TH with rollers	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	A	21	SB6321
39 x 25 x 23.125	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	A	21	SB6321
See Note G															
ERP035TH without rollers	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	A	21	SB6321
ERP040TH without rollers															
39 x 25 x 26.125															
See Note G															

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
ERP040DH, ERP050DH 40.625 x 28.3125 x 30.9375 Min. Battery Wt. - 3720 lbs.	80	40-D125-9	sp	38.80	500	125	9257	40	27.5	30.5625	3753		X	A	12	SBE6359
	80	40-H120-9	sp	37.25	480	120	9257	40	27.5	30.5625	3715		X	A	12	SBE6359
	80	40-P140-9	sp	43.46	560	140	9257	40	27.5	30.5625	3791		X	A	12	SBE6359
ERP050DH Optional Compartment ERP060DH 40.3125 x 33.9375 x 30.9375 Min. Battery Wt. - 4450 lbs.	80	40-D125-11	sp	48.50	625	125	9195	39.5	33	30.5625	4515		X	A	12	SBE6359
	80	40-H120-11	sp	46.56	600	120	9195	39.5	33	30.5625	4470		X	A	12	SBE6359
	80	40-P140-11	sp	54.32	700	140	9195	39.5	33	30.5625	4560		X	A	12	SBE6359
ERPS030TF with rollers 39 x 16.75 x 23.125 See Note F	36	18-D85-13		17.81	510	85	6062	37.6875	15.4375	22.625	1507		X	B	30	SB6320
	36	18-H80-13		16.76	480	80	6062	37.6875	15.4375	22.625	1447		X	B	30	SB6320
	36	18-P95-13		19.90	570	95	6062	37.6875	15.4375	22.625	1522		X	B	30	SB6320
ERPS030TF without rollers 39 x 16.75 x 26.125 See Note F	36	18-D100-13		20.95	600	100	6086	37.6875	15.4375	25.625	1718		X	B	30	SB6320
ERPS030TF with rollers 39 x 16.75 x 23.125 See Note G	48	24-D85-9		15.83	340	85	7151	37.6875	14.4375	22.625	1422		X	B	30	SB6321
	48	24-H80-9		14.90	320	80	7151	37.6875	14.4375	22.625	1365		X	B	30	SB6321
	48	24-P95-9		17.69	380	95	7151	37.6875	14.4375	22.625	1436		X	B	30	SB6321
ERO030STF without rollers 39 x 16.75 x 26.125 See Note G	48	24-D100-9		18.62	400	100	7050	37.6875	14.4375	25.625	1652		X	B	30	SB6321
ERC030TC 39 x 21 x 26.75	36	18-D100-17		27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	B	30	SB6320
	36	18-D85-17		23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	B	30	SB6320
	36	18-H80-17		22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	B	30	SB6320
	36	18-P95-17		26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	B	30	SB6320
ERC030TC 39 x 21 x 26.75	48	24-D100-13		27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	B	30	SB6320
	48	24-D85-13		23.75	510	85	7017	37.8125	20.5625	22.6875	2030		X	B	30	SB6320
	48	24-H80-13		22.35	480	80	7017	37.8125	20.5625	22.6875	1949		X	B	30	SB6320
	48	24-P95-13		26.54	570	95	7017	37.8125	20.5625	22.6875	2050		X	B	30	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
ERC030VA, ERC035VA	36	18-D85-19	26.71	765	85	6E46	35.25	27	22.6875	2345		X	B	20	SB6320
ERC040VA	36	18-D85-19	26.71	765	85	6226	34.9375	25.5625	22.6875	2274		X	B	20	SB6320
35.75 x 27.5625 x 23.5	36	18-H80-19	25.14	720	80	6E46	35.25	27	22.6875	2251		X	B	20	SB6320
	36	18-H80-19	25.14	720	80	6226	34.9375	25.5625	22.6875	2183		X	B	20	SB6320
	36	18-P95-19	29.86	855	95	6E46	35.25	27	22.6875	2368		X	B	20	SB6320
	36	18-P95-19	29.86	855	95	6226	34.9375	25.5625	22.6875	2297		X	B	20	SB6320
ERC030VA, ERC035VA	48	24-D85-15	27.70	595	85	7894	35.25	27	22.6875	2409		X	B	20	SB6321
ERC040VA	48	24-D85-15	27.70	595	85	7049	35.1875	25.5625	22.6875	2332		X	B	20	SB6321
35.75 x 27.5625 x 23.5	48	24-H80-15	26.07	560	80	7894	35.25	27	22.6875	2313		X	B	20	SB6321
	48	24-H80-15	26.07	560	80	7049	35.1875	25.5625	22.6875	2239		X	B	20	SB6321
	48	24-P95-15	30.96	665	95	7894	35.25	27	22.6875	2433		X	B	20	SB6321
	48	24-P95-15	30.96	665	95	7049	35.1875	25.5625	22.6875	2355		X	B	20	SB6321
ERC035BB	36	18-D85-21	29.68	850	85	6E67	37.75	26.5625	22.6875	2478		X	B	30	SB6320
38.25 x 27.0625 x 22.75	36	18-H80-21	27.94	800	80	6E67	37.75	26.5625	22.6875	2379		X	B	30	SB6320
	36	18-P95-21	33.17	950	95	6E67	37.75	26.5625	22.6875	2503		X	B	30	SB6320
ERC045VG, ERC050VG	36	18-D85-23	32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	20	SB6320
39.0625 x 27.5625 x 23.9375	36	18-H80-23	30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	20	SB6320
	36	18-P95-23	36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	20	SB6320
ERC045VG, ERC050VG	36	18-D85-25	35.62	1020	85	6030	38.1875	29.1875	22.6875	2924		X	B	20	SB6320
39.0625 x 30.9375 x 23.9375	36	18-H80-25	33.52	960	80	6030	38.1875	29.1875	22.6875	2807		X	B	20	SB6320
	36	18-P95-25	39.81	1140	95	6030	38.1875	29.1875	22.6875	2953		X	B	20	SB6320
ERC045VG, ERC050VG	36	18-D85-27	38.59	1105	85	6026	38.1875	31.4375	22.6875	3144		X	B	20	SB6320
ERC055VG, ERC060VG	36	18-H80-27	36.32	1040	80	6026	38.1875	31.4375	22.6875	3018		X	B	20	SB6320
39.0625 x 33.25 x 23.9375	36	18-P95-27	43.13	1235	95	6026	38.1875	31.4375	22.6875	3175		X	B	20	SB6320
ERC045VG, ERC050VG	48	24-D85-17	31.66	680	85	7002	38.1875	26.6875	22.6875	2695		X	B	20	SB6321
39.0625 x 27.5625 x 23.9375	48	24-H80-17	29.80	640	80	7002	38.1875	26.6875	22.6875	2587		X	B	20	SB6321
	48	24-P95-17	35.39	760	95	7002	38.1875	26.6875	22.6875	2722		X	B	20	SB6321
ERC045VG, ERC050VG	48	24-D85-19	35.62	765	85	7001	38.5625	30.4375	22.6875	2993		X	B	20	SB6321
39.0625 x 30.9375 x 23.9375	48	24-H80-19	33.52	720	80	7001	38.5625	30.4375	22.6875	2873		X	B	20	SB6321
	48	24-P95-19	39.81	855	95	7001	38.5625	30.4375	22.6875	3023		X	B	20	SB6321

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
ERC045VG, ERC050VG	48	24-D85-21	39.58	850	85	7004	38.1875	32.6875	22.6875	3272		X	B	20	SB6321
ERC055VG, ERC060VG	48	24-H80-21	37.25	800	80	7004	38.1875	32.6875	22.6875	3141		X	B	20	SB6321
39.0625 x 33.25 x 23.9375	48	24-P95-21	44.23	950	95	7004	38.1875	32.6875	22.6875	3305		X	B	20	SB6321
ERC045VG, ERC050VG	80	40-D85-9	26.38	340	85	9333	38	26.5	22.6875	2460		X	B	20	SB6320
39.0625 x 27.5625 x 23.9375	80	40-H80-9	24.83	320	80	9333	38	26.5	22.6875	2362		X	B	20	SB6320
	80	40-P95-9	29.49	380	95	9333	38	26.5	22.6875	2485		X	B	20	SB6320
ERC045VG, ERC050VG	80	40-D85-9	26.38	340	85	9334	38.1875	29.875	22.6875	2500		X	B	20	SB6320
39.0625 x 30.9375 x 23.9375	80	40-H80-9	24.83	320	80	9334	38.1875	29.875	22.6875	2400		X	B	20	SB6320
Min. Battery Wt. - 2500 lbs.	80	40-P95-9	29.49	380	95	9334	38.1875	29.875	22.6875	2525		X	B	20	SB6320
ERC045VG, ERC050VG	80	40-D85-11	32.98	425	85	9335	38	31.625	22.6875	2900		X	B	20	SB6320
ERC055VG, ERC060VG	80	40-H80-11	31.04	400	80	9335	38	31.625	22.6875	2784		X	B	20	SB6320
39.0625 x 33.25 x 23.9375	80	40-P95-11	36.86	475	95	9335	38	31.625	22.6875	2929		X	B	20	SB6320
Min. Battery Wt. - 2900 lbs.															
ERC065VG	36	18-D85-31	44.52	1275	85	6164	38.1875	35.9375	22.6875	3603		X	B	20	SB6320
39.0625 x 36.75 x 23.9375	36	18-H80-31	41.90	1200	80	6164	38.1875	35.9375	22.6875	3459		X	B	20	SB6320
	36	18-P95-31	49.76	1425	95	6164	38.1875	35.9375	22.6875	3639		X	B	20	SB6320
ERC065VG	36	18-D85-33	47.49	1360	85	6065	38.1875	38.1875	22.6875	3887		X	B	20	SB6320
40 x 39.0625 x 23.9375	36	18-H80-33	44.70	1280	80	6065	38.1875	38.1875	22.6875	3732		X	B	20	SB6320
	36	18-P95-33	53.08	1520	95	6065	38.1875	38.1875	22.6875	3926		X	B	20	SB6320
ERC065VG	48	24-D85-23	43.53	935	85	7059	38.1875	35.6875	22.6875	3573		X	B	20	SB6321
39.0625 x 36.75 x 23.9375	48	24-H80-23	40.97	880	80	7059	38.1875	35.6875	22.6875	3430		X	B	20	SB6321
	48	24-P95-23	48.66	1045	95	7059	38.1875	35.6875	22.6875	3609		X	B	20	SB6321
ERC065VG, ERC070VG	48	24-D85-25	47.49	1020	85	7019	39.5	38.5	22.6875	4120		X	B	20	SB6321
40 x 39.0625 x 23.9375	48	24-H80-25	44.70	960	80	7019	39.5	38.5	22.6875	3955		X	B	20	SB6321
	48	24-P95-25	53.08	1140	95	7019	39.5	38.5	22.6875	4161		X	B	20	SB6321
ERC065VG	80	40-D85-13	39.58	510	85	9005	38.1875	36.125	22.6875	3400		X	B	20	SB6320
39.0625 x 36.75 x 23.9375	80	40-H80-13	37.25	480	80	9005	38.1875	36.125	22.6875	3264		X	B	20	SB6320
	80	40-P95-13	44.23	570	95	9005	38.1875	36.125	22.6875	3434		X	B	20	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
ERC065VG, ERC070VG 40 x 39.0625 x 23.9375 Min. Battery Wt. - 3400 lbs.	80	40-D85-13	sp	39.58	510	85	9337	39	37.8125	22.6875	3400		X	B	20	SB6320
	80	40-H80-13	sp	37.25	480	80	9337	39	37.8125	22.6875	3264		X	B	20	SB6320
	80	40-P95-13	sp	44.23	570	95	9337	39	37.8125	22.6875	3434		X	B	20	SB6320
ERC070VG 40 x 39.0625 x 23.9375	36	18-D85-33		47.49	1360	85	6065	38.1875	38.1875	22.6875	3887		X	B	20	SB6320
	36	18-H80-33		44.70	1280	80	6065	38.1875	38.1875	22.6875	3732		X	B	20	SB6320
	36	18-P95-33		53.08	1520	95	6065	38.1875	38.1875	22.6875	3926		X	B	20	SB6320
ERP030VF, ERP030VT 39 x 21.5 x 23.9375	36	18-D85-17		23.75	680	85	6015	38.1875	20.0625	22.6875	2045		X	A	20	SB6320
	36	18-H80-17		22.35	640	80	6015	38.1875	20.0625	22.6875	1963		X	A	20	SB6320
	36	18-P95-17		26.54	760	95	6015	38.1875	20.0625	22.6875	2065		X	A	20	SB6320
ERP030VF, ERP030VT 39 x 21.5 x 26.75	36	18-D100-17		27.94	800	100	6060	38.1875	20.0625	25.6875	2322		X	A	20	SB6320
ERP030VF 39 x 21.5 x 23.9375	48	24-D85-13		23.75	510	85	7071	38.125	20.4375	22.6875	2022		X	A	20	SB6321
	48	24-H80-13		22.35	480	80	7071	38.125	20.4375	22.6875	1941		X	A	20	SB6321
	48	24-P95-13		26.54	570	95	7071	38.125	20.4375	22.6875	2042		X	A	20	SB6321
ERO939VF 39 x 21.5 x 26.75	48	24-D100-13		27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	A	20	SB6321
ERP030VT 39 x 21.5 x 23.9375	48	24-D85-13		23.75	510	85	7071	38.125	20.4375	22.6875	2022		X	B	20	SB6321
	48	24-H80-13		22.35	480	80	7071	38.125	20.4375	22.6875	1941		X	B	20	SB6321
	48	24-P95-13		26.54	570	95	7071	38.125	20.4375	22.6875	2042		X	B	20	SB6321
ERP030VT 39 x 21.5 x 26.75	48	24-D100-13		27.94	600	100	7106	37.875	20.5625	25.6875	2342		X	B	20	SB6321
ERP035VF, ERP040VF ERP040VT 39 x 25.25 x 23.9375	36	18-D85-21		29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	A	20	SB6320
	36	18-H80-21		27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	A	20	SB6320
	36	18-P95-21		33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	A	20	SB6320
ERP035VF, ERP040VF ERP040VT 39 x 25.25 x 26.75	36	18-D100-21		34.92	1000	100	6146	38.5	24.5625	25.6875	2529		X	A	20	SB6320

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SIT DOWN RIDERS (continued)

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Length Pos. (in.)		
ERP03VF, ERP040VF 39 x 25.25 x 23.9375	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	A	20	SB6321
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	A	20	SB6321
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	A	20	SB6321
ERP035VF, ERP040VF 39 x 25.25 x 26.75	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	A	20	SB6321
ERP035VT 39 x 25.25 x 23.9375	36	18-D85-21	29.68	850	85	6010	38.1875	24.5625	22.6875	2466		X	B	20	SB6320
	36	18-H80-21	27.94	800	80	6010	38.1875	24.5625	22.6875	2367		X	B	20	SB6320
	36	18-P95-21	33.17	950	95	6010	38.1875	24.5625	22.6875	2491		X	B	20	SB6320
ERP035VT 39 x 25.25 x 26.75	36	18-D100-21	34.92	1000	100	6146	38.5	24.5625	25.6875	2529		X	B	20	SB6320
ERP035VT, ERP040VT 39 x 25.25 x 23.9375	48	24-D85-15	27.70	595	85	7031	38.1875	23.5625	22.6875	2332		X	B	20	SB6321
	48	24-H80-15	26.07	560	80	7031	38.1875	23.5625	22.6875	2239		X	B	20	SB6321
	48	24-P95-15	30.96	665	95	7031	38.1875	23.5625	22.6875	2355		X	B	20	SB6321
ERP035 VT, ERP040VT 39 x 25.25 x 26.75	48	24-D100-15	32.59	700	100	7135	38.1875	23.5625	25.6875	2670		X	B	20	SB6321
ERP045VL, ERP050VL 40.75 x 28.25 x 31.25	80	40-D125-9	38.80	500	125	9257	40	27.5	30.5625	3753		X	B	20	EURO320
	80	40-H120-9	37.25	480	120	9257	40	27.5	30.5625	3715		X	B	20	EURO320
	80	40-P140-9	43.46	560	140	9257	40	27.5	30.5625	3791		X	B	20	EURO320
ERP060VL, ERP070VL 40.75 x 33.9375 x 31.25	80	40-D125-11	48.50	625	125	9195	39.5	33	30.5625	4515		X	A	20	EURO320
	80	40-H120-11	46.56	600	120	9195	39.5	33	30.5625	4470		X	A	20	EURO320
	80	40-P140-11	54.32	700	140	9195	39.5	33	30.5625	4560		X	A	20	EURO320

Note E - Battery requires 12 volt tap with 5/16" stainless steel stud and stainless steel nut.

Note F - Battery requires 18 volt tap with 5/16" stainless steel stud and stainless steel nut.

Note G - Battery requires 24 volt tap with 5/16" stainless steel stud and stainless steel nut.

Note H - These truck models require two (2) 18 cell, 36 volt batteries.

Note I - These truck models require two (2) 18 cell, 36 volt batteries in one tray wired parallel for 36 volt operation.

sp - Special tray IST9257 includes steel plates added for minimum weight requirement.

sp - Special tray IST9195 includes steel plates added for minimum weight requirement.

sp - Special tray IST9334 includes steel plates added for minimum weight requirement.

sp - Special tray IST9335 includes steel plates added for minimum weight requirement.

sp - Special tray IST9337 includes steel plates added for minimum weight requirement.

ea - KWH calculated for each 18 cell battery.

** Hinge runs through length.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.